Oracle8[™]Administrator's Reference for LINUX

Release 8.0.5 Standard Edition

September 1998

Part No. A66585-01

Topics Including: Optimal Flexible Architecture on Oracle8 Administering Oracle8 on LINUX Tuning Oracle8 on LINUX Administering SQL*Plus on LINUX Using Oracle Precompilers and the Oracle Call Interface on LINUX Configuring Oracle Net8 Running Oracle Data Cartridge Demos



Oracle8 Administrator's Reference for LINUX

Release 8.0.5

Part No. A66585-01

Copyright © 1998, Oracle Corporation. All rights reserved.

Primary Author: Kevin Kerr

Contributors: Kevin Adams, with Nicholas Hind, Nik Ormseth, and Lynn Robinson.

The programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be licensee's responsibility to take all appropriate fail-safe, back up, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and Oracle disclaims liability for any damages caused by such use of the Programs.

This Program contains proprietary information of Oracle Corporation; it is provided under a license agreement containing restrictions on use and disclosure and is also protected by copyright patent and other intellectual property law. Reverse engineering of the software is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. Oracle Corporation does not warrant that this document is error free.

If this Program is delivered to a U.S. Government Agency of the Department of Defense, then it is delivered with Restricted Rights and the following legend is applicable:

Restricted Rights Legend Programs delivered subject to the DOD FAR Supplement are 'commercial computer software' and use, duplication and disclosure of the Programs shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement. Otherwise, Programs delivered subject to the Federal Acquisition Regulations are 'restricted computer software' and use, duplication and disclosure of the Programs shall be subject to the restrictions in FAR 52...227-14, Rights in Data -- General, including Alternate III (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

Registered Trademarks of Oracle Corporation ConText, Oracle, the Oracle logo, Oracle Book, Oracle ConText, Oracle Names, Pro*Ada, Pro*COBOL, Pro*FORTRAN, Pro*Pascal, Pro*PL/I, SQL*Loader, SQL*Module, SQL*Net, and SQL*Plus are registered trademarks of Oracle Corporation.

Non-Registered Trademarks of Oracle Corporation Advanced Networking Option, Advanced Replication Option, Developer/2000, Enabling the Information Age, InterOffice, JDBC OCI Driver, JDBC Thin Driver, Network Computing Architecture, Oracle Applications, Oracle Call Interface, Oracle Data Gatherer, Oracle Enterprise Manager, Oracle Installer, Oracle InterOffice, Oracle Multiprotocol Interchange, Oracle Network Manager, Oracle Objects Option, Oracle Parallel Server, Oracle Parallel Server Management Components, Oracle Partitioning Option, Oracle Server Manager, Oracle Time Series Cartridge, Oracle Tenterprise Backup Utility, Oracle8, PL/SQL, Pro*C/C++, and Trusted Oracle are trademarks of Oracle Corporation.

Legato is a registered trademark in the United States, licensed exclusively through Legato. UNIX is a registered trademark in the United States and other countries, licensed exclusively through X/Open Company Limited. All other products or company names are used for identification purposes only, and may be trademarks of their respective owners.

For more information about Oracle's trademarks and intellectual property policies, contact the Oracle Legal Department at (650)506-5100.

Contents

Send Us Your Comments	
Preface	ix
Oracle8 and Oracle8 Enterprise Edition	ix
Typographic Conventions	х
Command Syntax	х

1 Optimal Flexible Architecture on Oracle8

Optimal Flexible Architecture (OFA)	1-2
Characteristics of OFA-Compliant Database	1-2
OFA Implemented on Oracle8 for LINUX	1-4
Naming Mount Points	1-4
Naming Directories	1-5
Naming Files	1-6
Naming Tablespaces	1-8
Exploiting OFA Structure for Oracle Files	1-8
OFA File Mapping	1-10
Raw Device Sizes	1-11
File Mapping for Multiple-Instance OFA Database	1-11
Directory Structure	1-13
Default OFA Database	1-17

2 Administering Oracle8 on Linux

Customizing the initsid.ora File	-2
----------------------------------	----

Sample initsid.ora File	2-2
Setting the Environment	2-4
Displaying and Setting Environment Variables	2-4
Setting a Common Environment	2-5
Database Examples	2-6
Environment Variables for Oracle8	2-7
Oracle Environment Variables on LINUX	2-7
LINUX Environment Variables Used with Oracle8	2-10
Setting the System Time	2-11
Estimating Oracle8 Server Memory Usage	2-12
Calculating Cluster Size and Index Size	2-13
Calculating Cluster Size	2-13
Calculating Index Size	2-13
Server Resource Limits	2-13
Initialization Parameters	2-14
Default Initialization Parameter Values	2-14
Controlling the System Global Area	2-15
Size limits of the SGA	2-16
Calculating the Size of the SGA	2-16
Relocating the SGA	2-17
Managing Special Accounts and Groups	2-18
	2-19
Managing Security	2-20
Groups and Security	2-20
Security for Oracle Server Utilities	2-21
Security for Server Manager Commands	2-21
Security for Database Files	2-21
Network Security	2-22
Enabling Automatic Logins for Oracle Net8	2-23
Checking Order	2-24
Security and Remote Passwords	2-25
Administering Login Home Directories	2-27
Building and Running Demonstrations	2-29
Loading PL/SQL Demonstrations	2-29
Running PL/SQL Demonstrations	2-30

SQL*Loader Demonstrations	2-31
Administering SQL*Loader	2-32
Oracle Security Server	2-34
Oracle8 Server SQL Reference	2-34
CREATE CONTROLFILE Parameters	2-34

3 Tuning Oracle8 on LINUX

The Importance of Tuning	3-2
Before Tuning the System	3-2
LINUX Tools	3-2
vmstat	3-2
free	3-3
SQL Scripts	3-3
utlbstat and utlestat SQL Scripts	3-3
Tuning Memory Management	3-3
Allocate Sufficient Swap Space	3-4
Control Paging	3-4
Hold the SGA in a Single Shared Memory Segment	3-5
Tuning Disk I/O	3-5
Tune the Database Writer to Increase Write Bandwidth	3-5
Monitoring Disk Performance	3-6
Disk Performance Issues	3-7
Tuning CPU Usage	3-7
Keep All Oracle Users/Processes at the Same Priority	3-7
Use Processor Affinity/Binding on Multi-Processor Systems	3-7
Use Single-Task Linking for Large Exports/Imports and SQL*Loader Jobs	3-8
Tuning Oracle Resource Contention	3-8
Tune LINUX Kernel Parameters	3-8
Tuning Block Size and File Size	3-9
Specifying Oracle Block Size	3-9
Tuning the LINUX Buffer Cache Size	3-9
Adjusting Cache Size	3-9
Using Trace and Alert Files	3-10
Trace File Names	3-10
Alert Files	3-10

4 Administering SQL*Plus on Linux

Administering SQL*Plus	4-2
Setup Files	4-2
The Site Profile	4-2
The User Profile	4-2
The PRODUCT_USER_PROFILE Table	4-3
Demonstration Tables	4-3
Help Facility	4-4
Using SQL*Plus	4-6
Using a System Editor from SQL*Plus	4-6
Setting the Order of the Editor	4-6
Setting the _editor option	4-6
Setting Environment Variables	4-6
Default Settings	4-7
Running Operating System Commands from SQL*Plus	4-7
Interrupting SQL*Plus	4-7
Using the SPOOL Command	4-8
Restrictions	4-8
COPY Command	4-8
Resizing Windows	4-8
Return Codes	4-8

5 Using Oracle Precompilers and the Oracle Call Interface on Linux

5-2
5-2
5-3
5-3
5-3
5-4
5-4
5-4
5-6
5-6
5-8
5-8

Undefined Symbols	5-9
Thread Support	5-9
Static and Dynamic Linking with Oracle Libraries	5-9
Using Signal Handlers	5-11
Signals	5-11
XA Functionality	5-14

6 Configuring Oracle Net8

Supplemental Documentation	6-2
Supplementary Information in README Files	6-2
Core Net8 Products and Features	6-3
Net8 Files and Utilities	6-3
Oracle Connection Manager	6-4
Multi-Threaded Server	6-4
Oracle Names	6-4
Oracle Net8 Protocol Adapters	6-4
The BEQ Protocol Adapter	6-5
Overview of the BEQ Protocol Adapter	6-5
Specifying a BEQ ADDRESS	6-6
The IPC Protocol Adapter	6-7
Overview of the IPC Protocol Adapter	6-7
Specifying an IPC ADDRESS	6-7
The TCP/IP Protocol Adapter	6-8
Overview of the TCP/IP Protocol Adapter	6-8
Specifying a TCP/IP ADDRESS	6-8
Net8 Naming Adapters	6-9
Oracle Enterprise Manager (OEM) Intelligent Agent	6-9
	6-9

Index

Send Us Your Comments

Oracle8 Administrator's Reference, Release 8.0.5 for LINUX

Part No. A66585-01

Oracle Corporation welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information used for revision.

- ⁿ Did you find any errors?
- ⁿ Is the information clearly presented?
- ⁿ Do you need more information? If so, where?
- ⁿ Are the examples correct? Do you need more examples?
- ⁿ What features did you like most about this manual?

If you find any errors or have other suggestions for improvement, please indicate the book title, part number, chapter, and section. You can send comments to us in the following ways:

Technical Publications Manager Platform Technologies Division Oracle Corporation 500 Oracle Parkway, Mailstop 10p2 Redwood Shores, CA 94065 USA

If you would like a reply, please give your name, postal or email address, and telephone number.

If you have problems with the software, please contact your local Oracle Support Services Center.

Preface

Purpose

This reference provides Linux-specific information required to successfully administer and tune the Oracle8 Server. This reference supplements information found in the Oracle8 and Oracle8 Enterprise Edition Documentation Set.

Audience

This document is intended for anyone responsible for administering the Oracle8 Server on a LINUX 2.0.34 system.

Oracle8 and Oracle8 Enterprise Edition

Unless noted otherwise, features and functionality described in this document are common to both Oracle8 and Oracle8 Enterprise Edition. For more information about Oracle8 Enterprise Edition-specific features and functionality, refer to the What's New section of the Release Notes.

Typographic Conventions

monospace	Monospace type indicates LINUX commands, directory names, path names, and filenames.
brackets []	Words enclosed in brackets indicate key names (for example, Press [Return]). Note that brackets have a different meaning when used in command syntax.
italics	Italic type indicates a variable, including variable portions of filenames, or emphasis.
UPPERCASE	Uppercase letters indicate Structured Query Language (SQL) commands, initialization parameters, or environment variables.

Because LINUX is case-sensitive, conventions in this document may differ from those used in Oracle product documentation.

Command Syntax

Command syntax appears in monospace font. The following conventions apply to command syntax:

backslash \	A backslash indicates a command that is too long to fit on a single line. Enter the line as printed (with a backslash) or enter it as a single line without a backslash: dd if=/dev/rdsk/c0tld0s6 of=/dev/rst0 bs=10b \ count=10000
braces { }	Braces indicate required items: .DEFINE {macrol}
brackets []	Brackets indicate optional items: cvtcrt termname [outfile]
	Note that brackets have a different meaning when used in regular text.
ellipses	Ellipses indicate an arbitrary number of similar items: CHKVAL fieldname valuel value2 valueN
italics	Italic type indicates a variable. Substitute a value for the variable: <i>library_name</i>
vertical line	A vertical line indicates a choice within braces or brackets: SIZE filesize [K/M]

Contacting Customer Support

Please copy this page and distribute it within your organization as necessary.

Oracle Support Services (OSS) can be reached at the following numbers (the hours are specified in your support contract):

- ⁿ In the United States, call: **1.650.506.1500**.
- ⁿ In Europe, call: +**44.1344.860160**.
- In Asia, call: +**81.3.5717.1860**.

Please prepare the following information before you call:

- ⁿ Your CSI number (if applicable) or complete contact details, including any special project information.
- ⁿ The release levels of the Oracle Server and associated products (for example, Oracle8 Server release 8.0.5.0, and Oracle Forms release 4.5.6.3.2).
- ⁿ Operating system name and release level, including patches and packages.
- ⁿ Details of error codes, numbers, and descriptions associated with the problem.
- ⁿ A full description of the issue, including:
 - ⁿ What happened? For example, the command used and result obtained.
 - ⁿ When did it happen? For example, time of day, or after a particular command, or after an operating system or Oracle upgrade.
 - ⁿ Where did it happen? For example, on a particular system, or within a particular procedure or table.
 - ⁿ What is the extent of the problem? For example, is your production system unavailable, or is the impact less severe? Is the problem getting worse?

Keep in mind what did not happen, as well as what did happen.

ⁿ Copies of any trace files, core dumps, or log files recorded near the time of the incident.

For installation-related problems, please have the following information available:

- ⁿ Listings of the contents of the ORACLE_HOME directory, and any staging area, if applicable.
- Contents of the installation log files in the \$ORACLE_HOME/orainst directory: install.log, sql.log, make.log, and os.log.

For more information, contact http://www.oracle.com/support.

Related Documentation

Advanced configuration and tuning recommended for a production database system is provided in the following manuals:

- ⁿ *Oracle8 Administrator's Guide*. Use this as a starting point for tasks associated with the Oracle8 Server, such as database creation, managing database objects, and creating users.
- n Net8 Administrator's Guide
- n Oracle8 Tuning

Unfamiliar with the concepts or terminology associated with relational database management systems? Read Chapter 1 in the *Oracle8 Concepts* before beginning your installation.

Ordering Documentation

- ⁿ In the United States, call Documentation Sales at: **1.800.252.0303**.
- ⁿ In the United Kingdom, call Oracle Direct Response at: +44.990.332200.
- ⁿ In other European countries, contact your local Oracle Support office.
- ⁿ In the Asia-Pacific region, contact your Oracle sales representative.

Shipping Inquiries

- ⁿ In the United States, call Client Relations at: **1.650.506.1500.**
- ⁿ In the United Kingdom, call Customer Relations at: +44.990.622300.
- ⁿ In other European countries, contact your local Oracle Support office.
- ⁿ In the Asia-Pacific region, contact your Oracle sales representative.

1

Optimal Flexible Architecture on Oracle8

- ⁿ Optimal Flexible Architecture (OFA)
- ⁿ OFA Implemented on Oracle8 for LINUX

Optimal Flexible Architecture (OFA)

Oracle Corporation recommends the Optimal Flexible Architecture (OFA) standard for Oracle8. The OFA standard is a set of configuration guidelines for fast, reliable Oracle databases that require little maintenance.

OFA is designed to:

- ⁿ organize large amounts of complicated software and data on disk to avoid device bottlenecks and poor performance
- ⁿ facilitate routine administrative tasks like software and data backup functions, which are often vulnerable to data corruption
- ⁿ alleviate switching among multiple Oracle databases
- ⁿ adequately manage and administer database growth
- ⁿ help eliminate fragmentation of free space in the data dictionary, isolate other fragmentation, and minimize resource contention

Characteristics of OFA-Compliant Database

An OFA-compliant database provides the following benefits:

File System Organization

The file system is organized to allow easy administration and accommodate scalability for:

- ⁿ adding data into existing databases
- n adding users
- n creating databases
- n adding hardware

Distributed I/O Loads

I/O loads are distributed across enough disk drives to prevent performance bottlenecks.

Hardware Support

Hardware costs are minimized only when it does not conflict with operational considerations.

Safeguards Against Drive Failures

By spreading applications across more than one drive, drive failures impact as few applications as possible.

Distribution of Home Directories

The following items can be distributed across more than one disk drive:

- ⁿ the collection of home directories
- ⁿ the contents of an individual home directory

Integrity of Login Home Directories

It is possible to add, move, or delete login home directories without having to revise programs that refer to them.

Independence of LINUX Directory Subtrees

Categories of files are separated into independent LINUX directory subtrees so that files in one category are minimally affected by operations on files in other categories.

Supports Concurrent Execution of Application Software

It is possible to execute multiple versions of applications software simultaneously, allowing the user to test and use a new release of an application before abandoning the previous version. Transferring to a new version after an upgrade is simple for the administrator and transparent for the user.

Distinguishes Administrative Information for each Database

The ability to separate administrative information about one database from that of another, ensures a reasonable structure for the organization and storage of administrative data.

Uses Consistent Database File Naming

Database files are named so that:

- ⁿ database files are easily distinguishable from all other files
- ⁿ files of one database are easily distinguishable from files of another database
- ⁿ control files, redo log files, and data files are identifiable as such
- ⁿ the association of data file to tablespace is clearly indicated

Separation of Tablespace Contents

Tablespace contents are separated to:

- ⁿ minimize tablespace free space fragmentation
- ⁿ minimize I/O request contention
- n maximize administrative flexibility

Tuning of I/O Loads across all Drives

I/O loads are tuned across all drives, including drives storing Oracle data in raw devices.

Additional Benefits of OFA for Parallel Server

For Oracle Parallel Server Installations:

- ⁿ administrative data is stored in a central place, accessible to all database administrators
- ⁿ administrative data for an instance is associated with the instance by the file name

OFA Implemented on Oracle8 for LINUX

A careful naming strategy for database files eliminates data administration problems. The OFA rules provided here correspond to the original OFA recommendations published in *The OFA Standard: Oracle8 for Open Systems*.

Naming Mount Points

Mount Point Syntax

Name all mount points using the syntax /pm, where p is a string constant and m is a unique fixed-length key (typically a two-digit number) used to distinguish each mount point. For example: /u01 and /u02, or /disk01 and /disk02.

Naming Mount Points for Very Large Databases (VLDBs)

If each disk drive contains database files from one application and there are enough drives for each database to ensure no I/O bottleneck, then use the syntax /q/dm for naming mount points, as explained in Table 1–1.

Table 1–1 Syntax for Naming Mount Points

q

a string denoting that Oracle data is stored here

	Syntax for Naming Mount Foints
dm	the value of the initialization parameter DB_NAME (synonymous with the
	instance <i>sid</i> for single-instance databases)

 Table 1–1
 Syntax for Naming Mount Points

For example, mount points named /u01/oradata/test01 and /u01/oradata/test02 allocate two drives for the Oracle test database.

Naming Directories

Home Directory Syntax

Name home directories using the syntax /pm/h/u, as explained in Table 1–2.

Table 1–2 Syntax for Naming Home Directories

h	a standard directory name
и	the name of the owner of the directory

For example, /u01/app/oracle is the Oracle server software owner home directory (also referred to as ORACLE_BASE and defaulted by the installer) and /u01/app/applmgr is an Oracle applications software owner home directory.

Placing home directories at the same level in the LINUX file system is advantageous for the following reason: it allows the collection of applications owner login home directories on different mount points, to be referred to with the single pattern matching string, /*/app/*.

Referring to Pathnames

Refer to explicit pathnames only in files designed specifically to store them, such as /etc/passwd and the Oracle oratab file. Refer to group memberships only in the /etc/group file.

Software Directories

h

In order to help fulfill the OFA requirement that it be possible to simultaneously execute multiple versions of application software, store each version of the Oracle8 Server software in a directory matching the pattern /pm/h/product/v, as explained in Table 1–3.

Table 1–3 Syntax for Naming Oracle8 Server Software Directories

a standard directory name

Table 1–3 Syntax for Naming Oracle8 Server Software Directories

,	the version	of the software

For example: /u01/app/oracle/product/8.0.5 indicates the start of the directory structure where the Oracle8 Server files are located. Set the ORACLE_HOME environment variable to this directory.

Naming Files

Administration Files

To facilitate the organization of administrative data, it is recommended that you store database-specific administration files in subdirectories according to h/admin/d/a/, where h is the Oracle software owner's home directory, d is the database name (DB_NAME), and a is a subdirectory for each of the following database administration files described in Table 1–4:

adhoc	ad hoc SQL scripts for a given database
arch	archived redo log files
adump	audit files (Set AUDIT_FILE_DEST in config <i>db_name</i> .ora to point here. This subdirectory should be cleaned out periodically).
bdump	background process trace files
cdump	core dump files
create	programs used to create the database
exp	database export files
logbook	files recording the status and history of the database
pfile	instance parameter files
udump	user SQL trace files

Table 1–4 Subdirectories for Database Administration Files

As an example, the subdirectory adhoc would have the following pathname, /u01/app/oracle/admin/sab/adhoc/

Database Files

The following naming convention for database files ensures that they are easily identifiable:

- ⁿ for control files, use /*pm/q/d*/control.ctl
- n for redo log files, use /pm/q/d/redon.log
- for data files use, /pm/q/d/tn. dbf

This syntax is explained in Table 1–5.

pm	a mount point name described earlier in this chapter
q	a string distinguishing Oracle data from all other files (usually named ORACLE or oradata)
d	the DB_NAME of the database
t	an Oracle tablespace name
n	a two-digit string

Table 1–5 Syntax for Naming Database Files

Note: Do not store files other than a control, redo log or data file associated with database *d* in the path /pm/q/d.

Following this convention could produce for example, a data file with the name, /u03/oradata/sab/system01.dbf, making it easy to see to which database the file belongs.

Separate Segments with Different Requirements

Separate groups of segments with different lifespans, I/O request demands, and backup frequencies across different tablespaces.

For each Oracle database, create the special tablespaces described in Table 1–6. These tablespaces are in addition to those needed for application segments.

Table 1-6Special TablespaceSYSTEMdata dictionary segmentsTEMPtemporary segmentsRBSrollback segmentsTOOLSgeneral-purpose toolsUSERSmiscellaneous user segments

Table 1–6 Special Tablespace

This method is effective because dictionary segments are never dropped, and no other segments that can be dropped are allowed in the SYSTEM tablespace. This ensures that the SYSTEM tablespace does not require a rebuild due to tablespace free space fragmentation.

Because rollback segments are not stored in tablespaces holding applications data, the administrator is not blocked from taking an application's tablespace offline for maintenance. The segments are partitioned physically by type, and the administrator can record and predict data growth rates without complicated tools.

Naming Tablespaces

Name tablespaces descriptively using a maximum of eight characters.

Although Oracle8 tablespace names can be thirty characters long, portable LINUX file names are restricted to fourteen characters. The recommended standard for a data file basename is tn. dbf, where t is a descriptive tablespace name and n is a two-digit string. Because the extension plus the two-digit string occupy a total of six characters, only eight characters remain for the tablespace name.

Descriptive names allow the name of a data file to be associated with the tablespace that uses it. For example, the names GLD and GLX might be used for the tablespaces storing General Ledger data and indices, respectively.

Note: Do not embed reminders of the word "tablespace" in your tablespace names. Tablespaces are distinguishable by context, and names do not need to convey information about type.

Exploiting OFA Structure for Oracle Files

Table 1–7 shows the syntax used for identifying classes of files.

Table 1–7	Directory	/ Structure	Syntax for	Identifying	Classes of Files
-----------	-----------	-------------	------------	-------------	------------------

/u[0-9][0-9]	user data directories
/*/home/*	user home directories
/*/app/*	user application software directories
/*/app/applmgr	Oracle apps software subtrees
/*/app/oracle/product	Oracle Server software subtrees
/*/app/oracle/product/8.0.5	Oracle Server 8.0.5 distribution files
/*/app/oracle/admin/sab	sab database administrative subtrees
/*/app/oracle/admin/sab/arch/*	sab database archived log files

/*/oradata	Oracle data directories
/*/oradata/sab/*	sab database files
/*/oradata/sab/*.log	sab database redo log files

Table 1–7 Directory Structure Syntax for Identifying Classes of Files

OFA File Mapping

Table 1–8 shows an hierarchical file mapping of a sample OFA-compliant database, including each file's mount point, application, database, and tablespace. The file names indicate the file type (control, log, or data).

-		•			
/					root mount point
u01	/				'user data' mount point #1
	app/				subtree for app software
		oracle/			home for <i>oracle</i> software owner
			admin/		subtree for database admin files
				TAR/	subtree for Support logs
				db_name1/	admin subtree for db_name1 database
				db_name2/	admin subtree for db_name2 database
			doc/		online documentation
			local/		subtree for local Oracle software
				aps6/	an Oracle6 admin package
				aps7/	an Oracle7 admin package
			product/		distribution files
				7.3.2/	ORACLE_HOME for 7.3.2 instances
				7.3.3/	ORACLE_HOME for 7.3.3 instances
				8.0.4/	ORACLE_HOME for 8.0.4 instances
	home/				subtree for login home directories
		ltb/			home for a user
		sbm/			home for a user
	oradat	a/			subtree for Oracle data
		db_name1/			subtree for <i>db_name1</i> database files
		db_name2/			subtree for <i>db_name2</i> database files
u02	2 /				'user data' mount point #2
	home/				subtree for login home directories
		cvm/			home for a user
		vrm/			home for a user
	oradat	a/			subtree for Oracle data
		db_name1/			subtree for <i>db_name1</i> database files
		db_name2/			subtree for <i>db_name2</i> database files
u03	3 /				'user data' mount point #3
	home/				subtree for login home directories
	oradat	a/			subtree for Oracle data
		db_name1/			subtree for <i>db_name1</i> database files
		db_name2/			subtree for <i>db_name2</i> database files

Table 1–8 Hierarchical File Mapping for OFA Installation

Raw Device Sizes

Choose a small set of standard sizes for all raw devices that may be used to store Oracle database files.

In general, standardizing on a single size is recommended. If a single size is used, raw files can be moved from one partition to another safely. The size should be small enough so that a fairly large number can be created, but large enough to be convenient.

For example, a 2 GB drive could be divided into 10 partitions of 200 MB each—a good balance between size and number. Any tablespace using raw devices should stripe them across several drives. If possible, the striping should be done with a logical volume manager.

File Mapping for Multiple-Instance OFA Database

Multiple-instance databases (Oracle Parallel Server installations) have an additional guideline for file mapping.

Administrative Home for Oracle Parallel Server

When using the Oracle Parallel Server, select one node to act as the Oracle *administrative home* for the cluster. The administrative home contains the administrative subtree. Create subdirectories for each instance accessing the database within the bdump, cdump, logbook, pfile, and udump directories of $\sim/admin/d/$. The admin directory for the administrative home should be mounted as the admin directory for every instance. An example is shown in Table 1–9.

u01/app/oracl	.e/admin/sab/		administrative directory for sab database
adhoc/			directory for miscellaneous scripts
arch/			log archive dest for all instances
	redo001.arc		archived redo log file
bdump/			directory for background dump files
	inst1/		background dump dest for <i>inst1</i> instance
	inst2/		background dump dest for inst2 instance
cdump/			directory for core dump files
	inst1/		core dump dest for inst1 instance
	inst2/		core dump dest for inst2 instance
create/			directory for creation scripts
	1-rdbms.sql		SQL script to create inst database
exp/			directory for exports
	970920full.dmp		Sept 20 full export dump file
	export/		directory for export parfiles
	import/		directory for import parfiles
logbook/			directory for inst logbook entries
	inst1/		directory for inst1 instance reports
		params.lst	v\$parameter report for inst1 instance
	inst2/		directory for inst2 instance reports
		params.lst	v\$parameter report for inst2 instance
	user.lst		dba_users report
pfile/			directory for instance parameter files
	inst1/		directory for inst1 instance parameters
		init	instance parameters for inst1 instance
	inst2/		directory for inst2 instance parameters
		init	instance parameters for inst2 instance
udump/			directory for user dump files
	inst1/		user dump dest for inst1 instance
	inst2/		user dump dest for inst2 instance

Table 1–9 Administrative Directory Structure for Dual-Instance Oracle Parallel Server

Directory Structure

ORACLE_BASE Directory

ORACLE_BASE is the root of the Oracle directory structure. ORACLE_BASE directory structure and content is described in Table 1–10. When installing an OFA-compliant database using the Oracle Installer, ORACLE_BASE is by default, set to /pm/app/oracle.

admin	administrative files
doc	online documentation
local	subtree for local Oracle software
product	Oracle software

Table 1–10 ORACLE_BASE Directory Structure and Content

ORACLE_HOME Directory

If you install an OFA-compliant Oracle Server, the ORACLE_HOME directory is /mount_point/app/oracle/product/*release_number*. ORACLE_HOME directory structure and content is described in Table 1–11. Under LINUX, the ORACLE_HOME directory contains the following subdirectories, as well as a subdirectory for each Oracle product:

bin	binaries for all products
ctx	ConText cartridge
dbs	init <i>sid</i> .ora, lk <i>sid</i>
jdbc	JDBC drivers
lib	Oracle product libraries
md	Spatial cartridge
mlx	Xerox Stemmer (for ConText cartridge)
network	Net8
nlsrtl	NLS runtime loadable data
ocommon	common files for all products
odg	data gatherer
opsm	Parallel Server Manager Components

 Table 1–11
 ORACLE_HOME Directory Structure and Content

oracore	core libraries
orainst	master installation files and programs
ord	data cartridges
otrace	Oracle TRACE
plsql	PL/SQL
precomp	precompilers
rdbms	server files and libraries required for the database
slax	SLAX parser
sqlplus	SQL*Plus
svrmgr	Server Manager

Table 1–11 ORACLE_HOME Directory Structure and Content

Oracle Product Subdirectories

Product subdirectories may include those described in Table 1–12, depending on the Oracle products available on your system and the products you purchase.

Table 1–12 Oracle Product Subdirectories

network	Oracle Net8
ocommon	libraries and SQL messages. All products depend on this directory, which is installed automatically
plsql	PL/SQL version 2, procedural option
sqlplus	SQL*Plus
svrmgr	Server Manager

Contents of Product Subdirectories

Each product subdirectory contains the subdirectories described in Table 1–13:

 Table 1–13
 Contents of Product Subdirectories

admin	administrative SQL and shell scripts (for example, catalog.sql, catexp.sql, and demo.sql)
admin/*	special directories for other products
admin/resource	resource files
admin/terminal	runtime terminal files

demo	demonstration scripts and datafiles
doc	README files (for example, readmeLINUX.doc)
install	product installation scripts
lib	product libraries and distributed makefiles
log	trace files and log files (for example, orasrv.log and *.trc files)
mesg	U.S. message files, and Multilingual Option (formerly National Language Support) message text and binary files (for example, oraus.msg and oraus.msb)

 Table 1–13
 Contents of Product Subdirectories

Examples of Product Subdirectories

Examples of product subdirectories and their contents are shown in Table 1–14.

 Table 1–14
 Examples of Product Subdirectories

rdbms	install, lib, admin, doc, mesg, log
sqlplus	install, demo, lib, admin, doc, mesg

File Naming Conventions in the admin Directory

The rdbms/admin directory contains the SQL scripts shown in Table 1–15.

Table 1–15 admin Directory, File Naming Conventions

cat*.sql	<pre>creates catalog and data dictionary tables and views. The following files are run automatically during installation: catalog.sql (for all installations) catproc.sql (for all installations) catparr.sql (for Parallel Server option installations) catrep.sql (for all installations)</pre>
dbms*.sql	additional database packages
utl*.sql	creates tables and views for database utilities

Filename Extensions

A description of filename extensions is shown in Table 1–16.

Table 1–16 Filename Extensions

. a object file libraries; Ada runtime libr	aries
---	-------

.ada	Ada source files
.aud	Oracle audit file
.bdf	X11 font description file
.bmp	X11 bitmap file
.C	C source file
.ctl	SQL*Loader control file; Oracle Server control file
.dat	SQL*Loader datafile
.dbf	Oracle Server tablespace file
.dei	ORCA de-installation script
.dmp	Export file
.doc	ASCII text file
.env	shell script file for setting environment
.f	FORTRAN source file
.h	C header file; also, sr.h is a SQL*Report Writer help file
.ins	ORCA installation script
.1	LINUX manual page
.lis	output of SQL*Plus scripts
.log	installation log files; Oracle Server redo log files
.map	Installer product component files
.mk	make files
.msb	NLS message file (binary)
.msg	NLS message file (text)
.0	object module
.ora	Oracle configuration files
.orc	installation prototype files
.pad	Pro*Ada source file
.pc	Pro*C source file
.pco	Pro*COBOL source file
.ppd	printer driver file
.pfo	Pro*FORTRAN source file

Table 1–16 Filename Extensions

.prd	product registration template file (for orainst)
.res	Toolkit II resource file
.sh	Bourne shell script file
.sql	SQL* script files
.sys	Bourne shell script file
.tab	SQL* script file
.trc	trace files
.tut	Bourne shell script file
.us	orainst message file
.utd	Uniform Terminal Definitions
.vrf	Installer Dependencies Verification Script

Table 1–16 Filename Extensions

Default OFA Database

An OFA default database created using the Oracle Installer is shown in Figure 1–1.

Figure 1–1 Default Oracle Installation



2

Administering Oracle8 on Linux

- ⁿ Customizing the initsid.ora File
- ⁿ Setting the Environment
- ⁿ Environment Variables for Oracle8
- ⁿ Estimating Oracle8 Server Memory Usage
- ⁿ Calculating Cluster Size and Index Size
- ⁿ Initialization Parameters
- ⁿ Controlling the System Global Area
- ⁿ Managing Special Accounts and Groups
- ⁿ Managing Security
- ⁿ Administering Login Home Directories
- ⁿ Building and Running Demonstrations
- n Oracle8 Server SQL Reference

Customizing the initsid.ora File

This section documents the default init*sid*.ora file provided with the Oracle8 distribution. The Oracle Installer creates it in the \$ORACLE_BASE/admin/*db_name*/pfile directory. You can modify it to customize your Oracle8 installation.

Some initsid.ora parameter settings are generic to any size installation. For those parameter settings requiring different values for different size installations, three scenarios are provided: small, medium, and large. In the sample initsid.ora file, parameters dependent on installation size are shown for each setting. You can comment out settings that do not apply to your installation by inserting a number sign (#) at the beginning of a line.

Table 2–1 suggests the approximate SGA sizes corresponding to the three scenarios provided for in the init*sid*.ora file.

Installation/Database Size				
Block Size	Small	Medium	Large	
2 KB	4500 KB	6800 KB	17000 KB	
4 KB	5500 KB	8800 KB	21000 KB	

Table 2–1 Block and SGA Sizes for Sample initsid.ora File

Sample initsid.ora File

This file is provided by Oracle Corporation to assist in customizing the RDBMS installation. Some parameter settings are generic to any size installation. For parameters that require different values in different size installations, three scenarios are provided: SMALL, MEDIUM and LARGE. Any parameter that needs to be tuned according to installation size will have three settings, each one commented according to installation size.

```
# replace DEFAULT with your database name
db name=DEFAULT
db files = 80
                                                                        # SMALL
# db_files = 400
                                                                        # MEDIUM
# db files = 1000
                                                                       # LARGE
db file multiblock read count = 8
                                                                        # SMALL
# db file multiblock read count = 16
                                                                       # MEDIUM
# db file multiblock read count = 32
                                                                        # LARGE
db block buffers = 100
                                                                        # SMALL
```

```
\# db block buffers = 550
                                                                       # MEDIUM
# db block buffers = 3200
                                                                       # LARGE
shared pool_size = 3500000
                                                                       # SMALL
# shared pool size = 5000000
                                                                       # MEDIUM
# shared_pool_size = 9000000
                                                                       # LARGE
log_checkpoint_interval = 10000
processes = 50
                                                                       # SMALL
# processes = 100
                                                                       # MEDIUM
# processes = 200
                                                                       # LARGE
parallel_max_servers = 5
                                                                       # SMALL
# parallel_max_servers = 4 x (number of CPUs)
                                                                       # MEDIUM
# parallel_max_servers = 4 x (number of CPUs)
                                                                       # LARGE
\log buffer = 8192
                                                                       # SMALL
\# \log buffer = 32768
                                                                       # MEDIUM
# log_buffer = 163840
                                                                       # LARGE
sequence cache entries = 10
                                                                       # SMALL
# sequence_cache_entries = 30
                                                                       # MEDIUM
# sequence cache entries = 100
                                                                       # LARGE
sequence_cache_hash_buckets = 10
                                                                       # SMALL
# sequence cache hash buckets = 23
                                                                       # MEDIUM
# sequence cache hash buckets = 89
                                                                       # LARGE
# audit_trail = true
                                # if you want auditing
# timed_statistics = true
                               # if you want timed statistics
max dump file size = 10240
                               # limit trace file size to 5 Meg each
# Uncommenting the line below will cause automatic archiving if archiving has
# been enabled using ALTER DATABASE ARCHIVELOG.
# log archive start = true
# log archive dest = disk$rdbms:[oracle.archive]
# log_archive_format = "T%TS%S.ARC"
# If using private rollback segments, place lines of the following
# form in each of your instance-specific init.ora files:
# rollback_segments = (name1, name2)
# If using public rollback segments, define how many
# rollback segments each instance will pick up, using the formula
```

```
# of rollback segments = transactions / transactions_per_rollback_segment
#
# In this example each instance will grab 40/10 = 4:
\# transactions = 40
# transactions_per_rollback_segment = 10
# Global Naming -- enforce that a dblink has same name as the db it connects to
global_names = TRUE
# Edit and uncomment the following line to provide the suffix that will be
# appended to the db_name parameter (separated with a dot) and stored as the
# global database name when a database is created. If your site uses
# Internet Domain names for e-mail, then the part of your e-mail address after
# the '@' is a good candidate for this parameter value.
# db domain = us.acme.com # global database name is db name.db domain
#_db_block_cache_protect = true
                                                      # memory protect buffers
#event = "10210 trace name context forever, level 2" # data block checking
#event = "10211 trace name context forever, level 2" # index block checking
#event = "10235 trace name context forever, level 1" # memory heap checking
#event = "10049 trace name context forever, level 2" # memory protect cursors
# define parallel server (multi-instance) parameters
#ifile = ora_system:initps.ora
# define two control files by default
control_files = (ora_control1, ora_control2)
# Uncomment the following line if you wish to enable the Oracle Trace product
# to trace server activity. This enables scheduling of server collections
# from the Oracle Enterprise Manager Console.
# Also, if the oracle_trace_collection_name parameter is non-null,
# every session will write to the named collection, as well as enabling you
# to schedule future collections from the console.
```

Setting the Environment

Displaying and Setting Environment Variables

oracle trace enable = TRUE

To display the value of an environment variable, use the echo command. For example, to display the value of ORACLE_SID, enter:
```
$ echo $ORACLE_SID
```

Setting and Exporting the Value of a Variable in a Current Session

For the Bourne or Korn shell, enter:

\$ ORACLE_SID=test
\$ export ORACLE_SID

For the C shell, enter:

% setenv ORACLE_SID test

where test is the value of the variable ORACLE_SID.

Setting a Common Environment

Oracle8 allows a DBA to set a common environment for all users. A common environment makes it easier for system administrators and database administrators to make changes to the physical Oracle Server system.

The oraenv Command File

The oraenv (coraenv for the C shell) command file is created during installation. It contains values for Oracle environment variables and provides:

- ⁿ a central means of updating all user accounts with database changes
- a mechanism for switching back and forth between Oracle Server databases

For example, a database needs to move from /usr/oracle to /usrl/oracle. Without a common environment-setting routine, user startup files would need to be updated individually. With oraenv, each user profile calls the oraenv command file and the changes must be made only to that file.

Local bin Directory

Placing oraenv (or coraenv) and dbhome in the local bin directory, separate from the Oracle software home directory, ensures that these files are accessible to all users. It also ensures that oraenv (coraenv) continues to work even if you change the path to point to a different ORACLE_HOME.

Moving Between Databases

To switch from one database or instance to another, call the oraenv routine, and reply to the prompt with the *sid* of the desired database. Always provide the full path of the oraenv command file. For example:

\$. /usr/local/bin/oraenv ORACLE_SID= [default]? sid

Database Examples

In the following examples, it is assumed your local bin directory is called /usr/local/bin and your production database is called PROD. If you prefer not to be prompted for the ORACLE_SID at startup, set the ORAENV_ASK environment variable to **no**.

In the examples below, ORAENV_ASK is reset to the default, **Yes**, after oraenv is executed. This ensures that the system prompts for a different ORACLE_SID the next time oraenv is executed.

Single Instance

For the Bourne or Korn shell, add or replace the following line in the .profile file:

```
. local_bin_directory/oraenv
```

with the following lines:

PATH=\${PATH}:/usr/local/bin ORACLE_SID=PROD export PATH ORACLE_SID ORAENV_ASK=N0 . oraenv ORAENV_ASK=

For the C shell, add or replace the following line in the .cshrc file:

source local_bin_directory/coraenv

with the following lines:

setenv PATH \${PATH}:/usr/local/bin
setenv ORACLE_SID PROD
set ORAENV_ASK = NO
source /usr/local/bin/coraenv
unset ORAENV_ASK

Multiple Instances

For multiple instances, define the *sid* at startup.

For the Bourne or Korn shell:

```
PATH=${PATH}:/usr/local/bin
```

```
ORACLE_SID=PROD
export PATH ORACLE_SID
SIDLIST= `awk -F: '/^[^#]/ {printf ``%s ", $1}' /etc/oratab`
echo ``SIDS on this machine are $SIDLIST"
ORAENV_ASK=
oraenv
```

For the C shell:

```
setenv PATH ${PATH}:/usr/local/bin
setenv ORACLE_SID PROD
set sidlist = `awk -F: '/^[^#]/ {printf ``%s ", $1}' /etc/oratab`
echo "SIDS on this machine are $sidlist"
unset ORAENV_ASK
source /usr/local/bin/coraenv
```

Environment Variables for Oracle8

Certain variables in the LINUX environment must be set prior to installation of the Oracle system.

See Also: Oracle8 Installation Guide.

Oracle Environment Variables on LINUX

Table 2-2 provides the syntax and examples for Oracle8 variables.

Variable Detail Definition EPC DISABLED Function Disables oracle trace true or false Syntax Example true NLS_LANG Function Specifies the language and character set used for output. See the Oracle8 Installation Guide for LINUX for a range of values. Syntax language_territory.characterset Example french_france.we8dec ORA_NLS33 Function Points to the directory where languages and character sets are stored. Set to \$ORACLE HOME/ocommon/nls/admin/data

Table 2–2 Oracle8 Environment Variables on LINUX

Variable	Detail	Definition
ORACLE_BASE	Function	Specifies the base of the Oracle directory structure for OFA-compliant databases.
	Syntax	directory_path
	Example	/mount_point/app/oracle
ORACLE_HELP	Function	Specifies the directory containing help files.
	Syntax	directory_path
	Example	<pre>\$ORACLE_HOME/help/admin/resource</pre>
ORACLE_HOME	Function	Specifies the directory containing the Oracle software distribution.
	Syntax	directory_path
	Example	/mount_point/app/oracle/product/release_number
ORACLE_PATH	Function	Specifies the search pathname for files used by Oracle applications, such as SQL*Plus. If not specified, the application reads from and writes to the current directory.
	Syntax	colon-separated list of directories directory: directory: directory
	Example	/u01/oracle/adhoc/sqlplus:. Note: The period adds the current working directory to the search path.
ORACLE_SID	Function	Specifies the Oracle System Identifier.
	Syntax	The string of numbers and characters must begin with a letter. For more information, see the <i>Oracle8 Installation Guide</i> for LINUX.
	Example	SAL1
ORACLE_TERM	Function	Specifies the terminal type identifier. Used by the Installer and Oracle products to determine the correct Toolkit II (.res) resource file. If not set, the value of the operating-system variable TERM is used.
	Syntax	string of characters
	Range of Values	The value of this variable must be set such that the pattern tk2c\${ORACLE_TERM}.res corresponds to valid resource files in the Toolkit II resource directory or directories. See the <i>Oracle8</i> <i>Installation Guide</i> for LINUX for a list of valid values.
	Example	vt100

Table 2–2 Oracle8 Environment Variables on LINUX

Variable	Detail	Definition
ORACLE_TERMINAL	Function	Specifies an additional directory to search for Toolkit II (.res) resource files.
	Syntax	directory_name
	Example	<pre>\$ORACLE_HOME/guicommon/tk21/admin/terminal</pre>
ORACLE_TRACE	Function	Turns on tracing of Bourne shell scripts during install. If set to \mathbf{T} , many Oracle shell scripts run with set- \mathbf{x} flag on.
	Range of Values	T or anything else.
ORAENV_ASK	Function	Controls whether (c)oraenv prompts for ORACLE_SID or ORACLE_HOME. If set to NO (c)oraenv does not prompt and, if set to anything else, it does.
	Syntax	string
	Range of Values	NO or anything else.
TNS_ADMIN	Function	Sets the directory containing the Oracle Net8 configuration files.
	Syntax	directory_path
	Range of Values	Any directory; for more information, see the <i>Oracle8 Installation Guide</i> for LINUX.
	Example	<pre>\$ORACLE_HOME/network/admin</pre>
TWO_TASK	Function	Sets the default Oracle Net8 connect string descriptor alias defined in the tnsnames.ora file.
	Syntax	available network alias
	Range of Values	Any valid Oracle Net8 alias defined in the tnsnames.ora file.
	Example	PRODDB_TCP

Table 2–2 Oracle8 Environment Variables on LINUX

_

Note: Environment variables should not be defined with names that are identical to names of Oracle Server processes, for example: arch, pmon, and dbwr.

Abbreviations for ORACLE_HOME and ORACLE_SID

In Oracle8 Server files and programs, a question mark (?) represents the value of ORACLE_HOME. For example, Oracle8 expands the question mark in the following SQL statement to the full pathname of ORACLE_HOME:

alter tablespace TEMP add datafile '?/dbs/dbs2.ora' size 2M

The @ sign represents \$ORACLE_SID. For example, to indicate that a file belongs to an instance, enter:

alter tablespace tablespace_name add datafile 'dbsfile@.ora'

LINUX Environment Variables Used with Oracle8

Table 2–3 provides the syntax and examples for LINUX environment variables used with Oracle8.

Variable	Detail	Definition
ADA_PATH	Function	Specifies the directory containing the Ada compiler.
DISPLAY	Function	Used by X-based tools. Specifies the display device used for input and output. See vendor's X Windows documentation for details.
	Syntax	hostname:display Hostname is the network identifier for the display device; display is a number which is almost always 0.
	Example	135.287.222.12:0 bambi:0
HOME	Function	The user's home directory.
LANG or LANGUAGE	Function	Specifies the language and character set used by the operating system for messages and other output. See the operating system documentation, and your <i>Oracle8 Installation Guide</i> for LINUX.
LDOPTS	Function	Specifies the default linker options on some platforms. See man pages on ld for details.
LPDEST	Function	Specifies the user's default printer for System V-based systems.
	Syntax	printer_name
	Example	docqms
LDPATH	Function	Default directories used by the linker to find shared object libraries. See man pages on ld for details.
LD_LIBRARY_PATH	Function	Used on some platforms by the shared library loader (ld.so) at runtime to find shared object libraries. See man pages on ld.so for details.
	Syntax	colon-separated list of directories directory:directory:directory
	Example	/usr/dt/lib:\$ORACLE_HOME/lib

Table 2–3 LINUX Environment Variables Used with Oracle8

Variable	Detail	Definition
РАТН	Function	Used by the shell to locate executable programs; needs to include \$ORACLE_HOME/bin.
	Syntax	colon-separated list of directories directory:directory:directory
	Example	/bin:/usr/bin:/usr/local/bin: /usr/bin/X11:\$ORACLE_HOME/bin:\$HOME/bin:. Note : The period adds the current working directory to the search path
PRINTER	Function	Selects the user's default printer for LINUX systems.
	Syntax	printer_name
	Example	docqms
SHELL	Function	Specifies the command interpreter used during a host command.
	Syntax	shell pathname
	Range of Values	/bin/sh or /bin/csh or /bin/ksh or any other command interpreter supplied with LINUX
	Example	/bin/sh
TERM	Function	Used by Oracle Toolkit II character mode tools to determine terminal types; also used by other LINUX tools for the same purpose.
	Example	vt100
TMPDIR	Function	Specifies the default directory for temporary disk files; if set, tools that create a temporary files do so in this directory.
	Syntax	directory_path
	Example	/u02/oracle/tmp
XENVIRONMENT	Function	Specifies a file containing X Windows system resource definitions. See your X Windows documentation for more information.

Table 2–3 LINUX Environment Variables Used with Oracle8

Setting the System Time

The TZ variable sets your time zone. Check your LINUX documentation to see if your operating system uses this environment variable.

It allows a user to adjust the clock for daylight saving time changes, or different time zones. The adjusted time is used to time-stamp files, produce the output of the date command, and obtain the current SYSDATE.

WARNING: Users are discouraged from changing their personal TZ value. Using different values of TZ such as GMT+24 may change the day a transaction is recorded. This affects Oracle applications that use SYSDATE, such as Oracle Financials. Use sequence numbers to order a table instead of date columns to avoid this problem.

Estimating Oracle8 Server Memory Usage

Before starting the Oracle8 Server, virtual memory requirements can be estimated using this formula:

<size of the oracle executable text>

- + <size of the SGA>
- + n * (<size of tool executables private data section>
 - + <size of oracle executables uninitialized data section>
 - + <8192 bytes for the stack>
 - + <2048 bytes for the processes user area>)

where n = number of background processes.

For each Oracle back-end connection, use the following formula to estimate virtual memory requirements:

<size of oracle executable data section>

- + <size of oracle executables uninitialized data section>
- + <8192 bytes for the stack>
- + <2048 bytes for processes user area>
- + <cursor area needed for the application>

Use the size command to estimate an executable's text size, private data section size, and uninitialized data section size (or *bss*). Program text is only counted once, no matter how many times the program is invoked, because all Oracle executable text is always shared.

To compute actual Oracle physical memory usage while the database is up and users are connecting to it, use the ps command. Look for all the front end, server, and background Oracle process entries. For each entry, add the "real size of process" columns for the resident memory use subtotal. Now add the text size for the Oracle executable and every other Oracle tool executable

running on the system to that subtotal. Remember to count executable sizes only once, regardless of how many times the executable was invoked.

See Also: Refer to your LINUX man pages or documentation for a list of available switches for the ps command.

Calculating Cluster Size and Index Size

Calculating Cluster Size

Use size guidelines in Table 2–4 to calculate cluster size using the formula in Appendix A of the *Oracle8 Administrator's Guide*.

Table 2–4 Cluster Size Values

Size
68 bytes
24*INITRANS value for the table
4 bytes per row of a clustered table

Calculating Index Size

Use Table 2–5 to calculate the size required by an index using the formula in Appendix A of the *Oracle8 Administrator's Guide*.

 Table 2–5
 Index Size Values

Туре	Size
Fixed header size	113 bytes
Variable transaction header	24*INITRANS value for the index
Entry header	5 bytes

Server Resource Limits

LINUX inherits resource limits from the parent process (see getrlimit(2) in your operating system documentation). These limits apply to the Oracle8 Server shadow process that executes for user processes. The LINUX default resource limits are high enough for any Oracle8 Server shadow or background process. However, if these limits are lowered, the Oracle8 Server system could be affected. Discuss this with your LINUX system manager.

Disk quotas established for the Oracle dba user ID may hinder the operation of the Oracle8 system. Confer with your Oracle8 database administrator and the LINUX system manager before establishing disk quotas.

Initialization Parameters

Initialization parameters can be modified in the init*sid*.ora file for the Oracle8 Server instance.

See Also: Oracle8 Administrator's Guide.

Default Initialization Parameter Values

Table 2–6 lists default initialization parameter values on LINUX. All Oracle8 Server instances assume these values if you do not specify different values for them in the initsid.ora file. Oracle Corporation recommends that you include in the initsid.ora file only those parameters that differ from the default initialization parameter values.

To display the current values of these parameters on the system, use Server Manager to execute the SQL statement SHOW PARAMETERS.

Parameter	Default Value
BACKGROUND_DUMP_DEST	<pre>\$ORACLE_BASE/admin/sid/bdump</pre>
BITMAP_MERGE_AREA_SIZE	1048576
COMMIT_POINT_STRENGTH	1
CONTROL_FILES	<pre>\$ORACLE_HOME/dbs/ctrl@.dbf (where @ represents ORACLE_SID)</pre>
CREATE_BITMAP_AREA_SIZE	8388608
DB_BLOCK_BUFFERS	200
DB_BLOCK_SIZE	2048
DB_FILES	80 (maximum of 2000000)
DB_FILE_DIRECT_IO_COUNT	64 (maximum of 1048576)
DB_FILE_MULTIBLOCK_READ_COUNT	8 (range of 1-128, but should not exceed one quarter of DB_BLOCK_BUFFERS)
DISTRIBUTED_TRANSACTIONS	16
HASH_AREA_SIZE	0
HASH MULTIBLOCK IO COUNT	1

Table 2–6 Default Initialization Parameters

See Also: Oracle8 Server Reference.

Parameter	Default Value
LOCK_SGA	FALSE
LOCK_SGA_AREAS	0
LOG_ARCHIVE_BUFFER_SIZE	64
LOG_ARCHIVE_BUFFERS	4 (maximum of 128)
LOG_ARCHIVE_DEST	<pre>\$ORACLE_HOME/dbs/arch/</pre>
LOG_ARCHIVE_FORMAT	"% t_% s.dbf"
LOG_BUFFER	8192
LOG_CHECKPOINT_INTERVAL	10000
LOG_SMALL_ENTRY_MAX_SIZE	80
MTS_MAX_DISPATCHERS	5
MTS_MAX_SERVERS	20
MTS_SERVERS	0
MTS_LISTENER_ADDRESS	ADDRESS=address (See Chapter 6)
NLS_LANGUAGE	AMERICAN
NLS_TERRITORY	AMERICA
OBJECT_CACHE_MAX_SIZE_PERCENT	10
OBJECT_CACHE_OPTIMAL_SIZE	102400
OPEN_CURSORS	50
OS_AUTHENT_PREFIX	ops\$
PROCESSES	50
SHARED_POOL_SIZE	3500000
SORT_AREA_SIZE	65536
SORT_READ_FAC	5
SORT_SPACEMAP_SIZE	512
USER_DUMP_DEST	<pre>\$ORACLE_BASE/admin/sid/udump</pre>

Table 2–6 Default Initialization Parameters

Controlling the System Global Area

The System Global Area (SGA) is the Oracle structure that resides in shared memory. It contains static data structures, locks, and data buffers. Sufficient shared memory must be available to each oracle process to address the entire SGA.

Size limits of the SGA

The maximum size of a single shared memory region is specified by the LINUX parameter SHMMAX. An SGA that is 2048 KB can use four shared memory regions of 512 KB each.

If the size of the SGA exceeds the maximum size of a shared memory segment (SHMMAX), Oracle8 attempts to attach more contiguous segments to fulfill the requested SGA size. SHMSEG is the maximum number of segments that can be attached by a process. To attach the segments at contiguous addresses, SHMMAX must be set to its maximum value on systems where its size is limited.

Note: Intimate Shared Memory (ISM) may cause problems when SHMMAX is smaller than the database SGA size.

The following init.ora parameters control the size of the SGA:

- DB_BLOCK_BUFFERS
- n DB_BLOCK_SIZE
- n SORT_AREA_SIZE
- n SHARED_POOL_SIZE

Use caution when setting values for these parameters. When values are set too high, too much of the machine's physical memory is devoted to shared memory resulting in poor performance. As a guideline, the total of all instance's SGA sizes should be no more than one-third of the total physical RAM.

Calculating the Size of the SGA

The approximate size of an instance's SGA can be calculated with this formula:

 $(DB_BLOCK_BUFFERS \times DB_BLOCK_SIZE)$

- + SORT_AREA_SIZE
- + SHARED_POOL_SIZE
- + 1MB

To display the size of the SGA for a running database in bytes, use the Server manager show sga command. This command displays the size of the SGA in bytes.

Relocating the SGA

The address at which the SGA is attached affects the amount of virtual address space available for such things as database buffers in the SGA and cursors in the user's application data area.

1. Determine the valid virtual address range for attaching shared memory segments (in the resulting tstshm display, the lines "Lowest shared memory address" and "Highest shared memory address" indicate the valid range):

```
$ tstshm
```

Note: The system may experience problems when executing tstshm while using Intimate Shared Memory (ISM).

- 2. Check the "Segment boundaries" output of tstshm to determine the valid virtual address boundaries at which a shared memory segment can be attached.
- **3.** Determine the size of your SGA. SGA size is displayed next to the heading Total System Global Area when your database system starts.
- 4. Move to the \$ORACLE_HOME/rdbms/lib directory, and run genksms to generate the file ksms.s:

```
$ cd $ORACLE_HOME/rdbms/lib
$ $ORACLE_HOME/bin/genksms -b sgabeg > ksms.s
```

where *sgabeg* is the starting address of the SGA (which defaults to 0x8000000), and should fall within the range determined in step 2.

- 5. Shut down the existing Oracle database.
- 6. Rebuild the oracle executable in the <code>\$ORACLE_HOME/rdbms/lib</code> directory:

```
$ make -f ins_rdbms.mk ksms.o
$ make -f ins_rdbms.mk ioracle
Using ioracle:
```

- ⁿ backs up the old executable (oracle0)
- assigns the correct privileges to the new oracle executable
- ⁿ moves the new executable into the \$ORACLE_HOME/bin directory

The result is a new Oracle kernel that loads the SGA at the address specified by sgabeg.

genksms -b

The genksms -b utility is used to adjust the starting point of fixed SGA.

Managing Special Accounts and Groups

The DBA should be familiar with special accounts required by the Oracle Server, and should make sure these accounts belong to the appropriate groups. The following section describes special user accounts. LINUX accounts are described in Table 2–7, Oracle server accounts are described in Table 2–8.

Table 2–7	LINUX	Accounts
-----------	-------	----------

oracle	The <i>oracle</i> software owner represents the account that owns the Oracle8 software. This maintenance account requires DBA privileges in order to CREATE, STARTUP, SHUTDOWN, and CONNECT as INTERNAL to the database. The <i>oracle</i> software owner must never be the superuser.
root	The root user is a special LINUX account with maximum privileges (called superuser privileges). This account is used to configure the LINUX kernel, configure and install networking software, and create user accounts and groups.

Table 2–8 Oracle Server Accounts

SYS	This is a standard Oracle8 account with DBA privileges automatically created during installation. The SYS account owns all the base tables for the data dictionary. This account is used by the DBA.
SYSTEM	This account is also a standard Oracle8 account, with DBA privileges automatically created during installation. Additional tables or views can be created by the SYSTEM user. DBAs may log in as SYSTEM to monitor or maintain databases.

Table 2–9 Special Group Accounts

•

dba group	The <i>oracle</i> software owner is the only required member of the dba group. You can add the root user, or any other LINUX user, to the dba group. Members of this group have access to Server Manager specially privileged functions. If your account is not a member of the dba group, you must enter a password in order to connect as INTERNAL or gain access to the other administrative functions of Server Manager. The default group ID is dba.
oper group	This is an optional LINUX group you can create. Members have database OPERATOR privileges. OPERATOR privileges are a restricted set of dba privileges.
root group	Only the root user should be a member of the root group.

Managing Security

Oracle8 uses several features of the LINUX operating system to provide a secure environment for users. These features include file ownership, group accounts, and the ability of a program to change its user ID upon execution.

The two-task architecture of Oracle8 improves security by dividing work (and address space) between the user program and the oracle program. All database access is achieved through the shadow process and special authorizations on the oracle program.

Groups and Security

To ensure greater security on an Oracle8 database, create user groups at the operating system level. Groups are controlled by the LINUX file /etc/group. Oracle programs are divided into two sets for security purposes: those executable by all (*other*, in LINUX terms), and those executable by DBAs only. A recommended approach to security is:

- ⁿ Before installing the Oracle Server, create a database administrators' group (dba) and assign the root and *oracle* software owner IDs to this group. Programs executable by dba only have permission 710. Server Manager system-privileged commands are assigned automatically to the dba group upon installation.
- Add an oracle group of authorized users to allow a subset of LINUX users limited access to Oracle8. Give Oracle utilities the oracle group ID. Publicly executable programs, such as SQL*Plus, should be executable by this group. Set the permissions on the utilities to 710 to grant execute permissions to this group, but not *other*.
- ⁿ Grant permission 711 to programs executable by *other*. Restrict this permission to programs that do not affect database security.

Although you can assign any name to the database administrators' group, dba is the default group name, and the convention used in this document. If you change this group name, the Oracle Installer relinks the kernel automatically during Installation. If you have multiple databases with the same ORACLE_HOME (a configuration which Oracle Corporation *strongly* discourages), they should have the same database administrators' group. These restrictions do not apply to the group name for ordinary users (known as the oracle group).

WARNING: Even though both the *oracle* software owner and root user should belong to the dba group, the *oracle* software owner should *not* be a member of the root group. The root user should be the *only* member of the root group.

Security for Oracle Server Utilities

Protect the Oracle8 executables from unauthorized use. The method you use depends on your environment and whether you use single-task utilities. These are suggestions for protecting Oracle8 executables:

- ⁿ Keep all programs in the \$ORACLE_HOME/bin directory and give ownership to the *oracle* software owner.
- ⁿ Give all user utilities (sqlplus, exp, imp) a protection of 711 so all users on the machine can access the Oracle Server.
- ⁿ Give all DBA utilities (such as Server Manager) a protection of 700 to restrict the use of these utilities to the DBA username, usually the *oracle* software owner.

Security for Server Manager Commands

If you do not have SQL*Plus, you can use Server Manager to make SQL queries. However, be careful how you assign access to Server Manager. The following system-privileged statements should not be accessible to anyone but the *oracle* software owner and the dba group users, as they grant special operating system privileges:

- n STARTUP
- n SHUTDOWN
- n CONNECT INTERNAL

WARNING: System-privileged statements can damage your database if used incorrectly. Note that non-dba group users can connect as internal if they have the necessary password.

Security for Database Files

The user ID used to install Oracle8 should own the database files. The default user ID is the *oracle* software owner. Set the authorizations on these files to permission 0600: read/write (rw) by owner only, with no write authorizations for group or other users.

The *oracle* software owner should own the directories containing the database files. For added security, revoke read permission from *group* and other users.

To access the protected database files, the oracle program must have its set user ID (setuid) bit on. To set this bit, enter:

```
$ chmod 6751 $ORACLE_HOME/bin/oracle
```

This sets the authorization for the oracle program to:

-rwsr-s--x 1 oracle dba 443578 Mar 10 23:03 oracle

Setting the User ID

The Oracle Installer automatically sets the user ID. The s in the user execute field means when you execute the oracle program, it has an effective user ID of *oracle*, regardless of the actual user ID of the person invoking it.

Network Security

Using Passwords on the Network

Remote users on the network can enter their passwords in clear or encrypted text. When you use clear text, passwords can be picked up by unauthorized users, resulting in a breach of security. Oracle Net8 supports encrypted passwords.

DBA Privileges Over the Network

To control DBA privileges over the network choose one of the following options:

- set remote DBA access to denied in the /var/opt/oracle/listener.ora
 file
- set a special password in orapwd for DBA privileges

Automatic (ops\$) Logins

Oracle8 supports automatic logins (operating system authorized logins) over the network.

LINUX treats a dollar sign (\$) as the beginning of an environment variable. Therefore, when you specify an operating system authorized (ops\$) login on the command line or in a script, first escape the \$ with a backslash (\). For example, user ID scott should specify ops\\$scott when logging in remotely.

Automatic logins are not allowed for the root user ID.

Note: Automatic logins by PC, Apple MacIntosh, and OS/2 users are not secure. Anyone can edit the Oracle configuration file and change their user ID. For security reasons, if users of these systems are logging in over the network, Oracle Corporation strongly recommends you disable the ops\$ logins in the listener.ora file.

Enabling Automatic Logins for Oracle Net8

Automatic and remote DBA logins are not controlled by Oracle Net8. They are controlled by the Oracle8 Server and configured using parameters in the init*sid*.ora file. Although automatic logins are supported, they are disabled by default. To enable them, set the REMOTE_OS_AUTHENT initialization parameter to true, then start up the database.

Because oracle controls these logins, it is not necessary to run the Oracle Net8 listener as setuid to root.

See Also: Configuring Oracle Net8 is described in Chapter 6.

To perform an automatic login with Oracle Net8, create a user called daemon in your /etc/passwd file. The daemon user must not have an ops\$ account in any of the local databases, nor be in any of the DBA groups. That is, there should be no ops\$daemon account that would allow an outside user to intrude into your local database.

DBA Group ID Keywords

Table 2–10 describes the keywords used in the /var/opt/oracle/listener.ora file to enable and control remote logins:

DBA_GROUP	Use this keyword if the name is constant for all instances serviced by the listener.
DBA_GROUP_sid	Use this keyword for each ORACLE_SID if the listener services more than one \$ORACLE_HOME, and the group IDs are different.
OPS_DOLLAR_LOGIN_ALLOWED	Use these keywords to control remote login.
OPS_DOLLAR_LOGIN_DENIED	OPS_DOLLAR_LOGIN_DENIED is the default.
REMOTE_DBA_OPS_ALLOWED	Use these keywords to control remote DBA access.
REMOTE_DBA_OPS_DENIED	REMOTE_DBA_OPS_DENIED is the default.

Table 2–10Keywords Used to Control Remote Logins

If the DBA group ID for the database accessed is not the default name (dba), you can specify a non-default name.

Set remote login and remote DBA access parameters to the individual ORACLE_SIDs of databases on the network, or specify all *sids* at once. For example, either of the following statements are valid:

PARAMETER=ALL_SIDS
PARAMETER=sid1[, sidn...]

To see which privileges are assigned to the *sids*, enter:

```
$ lsnrctl status
```

Checking Order

The system checks remote login parameters in the following order:

- 1. parameters that deny access
- 2. parameters that permit access
- 3. the default value (denied)

These privileges are implemented by manipulating the user ID and group ID of the shadow process forked by the Oracle Net8 listener. For example:

- If OPS_DOLLAR_LOGIN_DENIED is true for a particular instance, or if the user ID as reported by the client-side operating system has no account on the database host machine, the user ID and group ID are found in the /etc/passwd file under the entry for daemon.
- ⁿ If both OPS_DOLLAR_LOGIN_ALLOWED and REMOTE_DBA_OPS_ALLOWED are true for a particular ORACLE_SID, and if the user ID as reported by the client

operating system does have an account on this system, the user ID and group ID are found in /etc/passwd for this user ID.

If OPS_DOLLAR_LOGIN_ALLOWED is true for a particular ORACLE_SID, but REMOTE_DBA_OPS_ALLOWED is false, then, if the user ID has DBA privileges, the process has the user ID and group ID of daemon. Otherwise, the process has the user ID and group ID of this user.

Note: REMOTE_DBA_OPS_ALLOWED is false by default. Oracle Corporation recommends that you do not change this value. When this parameter is set to false, users with DBA privileges cannot make operating system authorized logins over the network. They can, however, proceed with ordinary (password-protected) network logins.

Security and Remote Passwords

n

You can access or administer a database from a remote machine, such as a personal computer, without operating system accounts. User validation is accomplished by using an Oracle8 password file, created and managed by the orapwd utility. You can also use password file validation on systems that support operating system accounts.

Local password files are in the \$ORACLE_HOME/dbs directory and contain the username and password information for a single database. If there are multiple \$ORACLE_HOME directories on a machine, each has a separate password file.

Running orapwd

The orapwd utility exists in \$ORACLE_HOME/bin and is run by the *oracle* software owner. Invoke orapwd by entering:

\$ orapwd file=\$ORACLE_HOME/dbs/orapwsid password=password entries=max_users

This syntax is described in Table 2–11:

Table 2–11 Syntax for Executing orapwd

file	is the name of the file where password information is written. The name of the file must be orapw <i>sid</i> , and you must supply the full pathname. Its contents are encrypted and not user-readable. This parameter is mandatory.
password	is the initial password you selected for INTERNAL and SYS. You can change this password after you create the database using an ALTER USER statement. This parameter is mandatory.

entries	is the maximum number of users allowed to connect to the database
	as SYSDBA or SYSOPER. This parameter is mandatory only if you
	want this password file to be EXCLUSIVE.

Table 2–11 Syntax for Executing orapwd

Note: You must create a new password file if you ever need to increase the maximum number of users. Therefore, set *max_users* to a higher number than you expect to require.

orapwd Example

```
$ orapwd file=/u01/app/oracle/product/8.0.5/dbs/orapwV805 \
password=manager entries=30
```

See Also: Oracle8 Server Administrator's Guide.

Shared Password File for Multiple Databases

The default password file /dbs/orapwd should be used when the initialization parameter REMOTE_LOGIN_PASSWORDFILE is set to SHARED for multiple databases. There is no *sid* specific password file for multiple databases.

Access to a Database from a Remote PC

When there is an Oracle8 password file, networked PC users can access this database as INTERNAL. Non-privileged users can connect to the database by invoking an Oracle application that uses the database. Privileged users who want to perform DBA functions on the database can enter the appropriate Server Manager command from their PC, adding the dba user password. For example:

```
SVRMGR> connect internal/dba_password
```

To connect as OPERATOR, use the same command with the OPERATOR password.

Remote Authentication

The following init*sid*.ora parameters, shown in Table 2–12 control the behavior of remote connections through non-secure protocols:

 Table 2–12
 Parameters For Controlling Remote Connections

REMOTE_OS_AUTHENT	enables or disables ops\$ connection
OS_AUTHENT_PREFIX	used by ops\$ accounts
REMOTE_OS_ROLES	enables or disables roles through remote connections

Note: If REMOTE_OS_AUTHENT is set to true, users who are members of the dba group on the remote machine are able to connect as INTERNAL without a password.

User-Visible Effects of the Shutdown Mechanism

Clients connected to an Oracle instance while a shutdown takes place will receive one of the following error messages upon subsequent SQL operations.

```
ORA-03113: end-of-file on communication channel ORA-12571: TNS:packet writer failure
```

Administering Login Home Directories

To add or move login home directories without modifying programs that refer to them, you must:

- refer to explicit path names in files designed to store them, for example: /etc/passwd and /etc/oratab
- ⁿ refer to group memberships in the /etc/group file

It is not necessary to record a pathname except in a central reference file, because a user's home directory can be derived in either of the following ways:

- ⁿ C shell and Korn shell users can use ~*login* to refer to a user's home directory.
- ⁿ Bourne shell users can construct a simple program to do this. See the sample lhd script later in this section.

Similarly, group memberships are computed from /etc/group. See the sample grpx script later in this section.

Note: Local general-purpose utilities such as these should be stored in the /var/opt/bin directory.

Sample Ihd Script

_

```
#!/bin/sh
#
# lhd - print login home directory name for a given user
#
# SYNTAX
# lhd [login]
#
prog='basename $0'
if [ $# -eq 0 ] ; then
   login=`whoami`
elif [ $# -eq 1 ] ; then
   login=$1
else
   echo "Usage: $prog login" >&2
   exit 2
fi
awk -F: '$1==login {print $6}' login=$login /etc/passwd
```

Sample grpx Script

```
#!/bin/sh
# grpx - print the list of users belonging to a given group
#
prog='basename $0'
if [ $# -ne 1 ] ; then
   echo "Usage: $prog group" >&2
   exit 2
fi
g=$1
# calculate group id of g
gid='awk -F: '$1==g {print $3}' g=$g /etc/group'
# list users whose default group id is gid
ul=`awk -F: '$4==gid {print $1}' gid=$gid /etc/passwd`
# list users who are recorded members of g
u2=`awk -F: '$1==g {gsub(/,/," "); print $4}' g=$g /etc/group`
# remove duplicates from the union of the two lists
echo $u1 $u2 | tr " " "\012" | sort | uniq | tr "\012" " "
echo
```

Example 2–1 Using Ihd and grpx Scripts

This example shows how the administrator can propagate a skeleton .profile file to the home directory for each member of a group. If the membership list of the clerk group changes, the code does not require modification.

```
$ for u in 'grpx clerk' ; do
> cp /etc/skel/.profile 'lhd $u'
> done
```

Building and Running Demonstrations

Loading PL/SQL Demonstrations

PL/SQL includes a number of sample programs you can load. Demonstration and message files are in the rdbms directory. Perform these steps with the Oracle8 Server open and mounted:

1. Invoke Server Manager and connect with the user/password scott/tiger:

```
$ cd $ORACLE_HOME/plsql/demo
$ svrmgrl
SVRMGR > connect scott/tiger
```

2. To load the demonstrations, invoke exampbld.sql from Server Manager:

SVRMGR > @exampbld

Note: Build the demonstrations under any Oracle account with sufficient permissions. Run the demonstrations under the same account you used to build them.

Running PL/SQL Demonstrations

Table 2–13 lists the kernel demonstrations.

Table 2–13 Kernel Demonstrations

examp1.sql	examp5.sql	examp11.sql	sample1.sql
examp2.sql	examp6.sql	examp12.sql	sample2.sql
examp3.sql	examp7.sql	examp13.sql	sample3.sql
examp4.sql	examp8.sql	examp14.sql	sample4.sql
extproc.sql			

Table 2–14 lists the precompiler demonstrations.

Table 2–14	Precompiler Demonstrations
------------	----------------------------

examp9.pc	examp10.pc	sample5.pc	sample6.pc

To run the kernel PL/SQL demonstrations, invoke SQL*Plus to connect to the kernel, using the same user/password you used to create the demonstrations. Start the demonstration by typing an "at" sign (@) or the word start before the demonstration name. For example, to start the exampl demonstration, enter:

```
$ sqlplus scott/tiger
SQLPLUS > @examp1
```

To build the precompiler PL/SQL demonstrations, enter:

```
$ cd $ORACLE_HOME/plsql/demo
$ make -f demo_plsql.mk demos
```

If you want to build a single demonstration, enter its name as the argument in the make command. For example, to make the examp9.pc executable, enter:

```
$ make -f demo_plsql.mk examp9
```

To start the examp9 demonstration from your current shell, enter:

\$ examp9

In order to run the extproc demo, you first have to add the following line to the file, tnsnames.ora:

```
(DESCRIPTION=(ADDRESS=(PROTOCOL=ipc)(KEY=plsff))(CONNECT_DATA=(SID=extproc)))
```

and the following line to the file, listener.ora:

SC=(SID_NAME=extproc)(ORACLE_HOME=/vobs/oracle)(PROGRAM=extproc))

then from your current shell, enter:

SVRMGR> connect scott/tiger Connected. SVRMGR> connect system/manager Connected. SVRMGR> grant create library to scott; Statement processed. SVRMGR> connect scott/tiger Connected. SVRMGR> create library demolib as '\$ORACLE_HOME/plsql/demo/extproc.so'; Statement processed.

Then finally, to run the tests:

SVRMGR> connect scott/tiger Connected. SVRMGR> @extproc

SQL*Loader Demonstrations

SQL*Loader demonstrations require that:

- ⁿ the user scott/tiger has CONNECT and RESOURCE privileges
- ⁿ the EMP and DEPT tables exist and are empty

To create and run a demonstration:

- 1. Connect to the database as the user/password scott/tiger from Server Manager (line mode).
- 2. Run the ulcasen.sql corresponding to the demonstration you want to run.
- 3. As scott/tiger, invoke the demonstration from the command line:

\$ sqlldr scott/tiger ulcasen

As scott/tiger, run the SQL*Loader demonstrations in the following order:

- " ulcase1: Follow steps 1 3 above.
- " ulcase3: Follow steps 1 3 above.
- " ulcase4: Follow steps 1 3 above.
- " ulcase5: Run the ulcase*.sql script as scott/tiger, then enter the following at the command line:

\$ sqlldr scott/tiger ulcase*

- ulcase2: Invoke the demonstration (you do not have to run the ulcase2.sql script).
- ulcase6: Run the ulcase6.sql script as scott/tiger, then enter the following at the command line:

\$ sqlldr scott/tiger ulcase1 DIRECT=true

" ulcase7:Run the ulcase6.sql script as scott/tiger, then enter the following at the command line:

\$ sqlldr scott/tiger ulcase7

Administering SQL*Loader

Oracle8 Server incorporates SQL*Loader functionality. Demonstration and message files are in the rdbms directory.

File Processing Option

The SQL*Loader release 1.1 control file includes the following additional file processing option strings, the default being str, which takes no argument:

```
[ "str" | "fix n" | "var n" ]
```

str (the default) specifies a stream of records, each terminated by a newline character, which are read in one record at a time.

fix indicates that the file consists of fixed-length records, each of which is n bytes long, where n is an integer value.

var indicates that the file consists of variable-length records, each of which is n bytes long, where n is an integer value specified in the first five characters of the record.

If the file processing options are not selected, the information is processed by default as a stream of records (str). You might find that fix mode yields faster performance than the default str mode because it does not need to scan for record terminators.

Newlines in Fixed Length Records

When using the fix option to read a file containing fixed-length records, where each record is terminated by a newline, include the length of the newline (one character) when specifying the record length to SQL *Loader.

For example, to read the following file:

AAA newline BBB newline CCC newline

specify fix 4 instead of fix 3 to account for the additional newline character.

If you do not terminate the last record in a file of fixed records with a newline character, do not terminate the other records with a newline character either. Similarly, if you terminate the last record with a newline, terminate all records with a newline.

WARNING: Certain text editors, such as vi, automatically terminate the last record of a file with a newline character. This leads to inconsistencies if the other records in the file are not terminated with newline characters.

Removing Newlines

Use the position(x:y) function in the control file to discard the newlines from fixed length records rather than loading them. To do this, enter the following in your control file:

```
load data
infile xyz.dat "fix 4"
into table abc
( dept position(01:03) char )
```

When this is done, newlines are discarded because they are in the fourth position in each fixed-length record.

Oracle Security Server

See Also: For information on the Oracle Security Server, see the Oracle Security Server Guide.

Oracle8 Server SQL Reference

CREATE CONTROLFILE Parameters

Use the parameter values in Table 2–15 to determine the size of control files for a database.

Parameter **Default Value** Maximum Value MAXDATAFILES 30 65534 1 63 MAXINSTANCES 255 MAXLOGFILES 16 MAXLOGMEMBERS 2 5 100 MAXLOGHISTORY 65534

Table 2–15 Determining the Size of Control Files

3

Tuning Oracle8 on LINUX

- ⁿ The Importance of Tuning
- n LINUX Tools
- ⁿ SQL Scripts
- ⁿ Tuning Memory Management
- ⁿ Tuning Disk I/O
- ⁿ Monitoring Disk Performance
- ⁿ Tuning CPU Usage
- ⁿ Tuning Oracle Resource Contention
- ⁿ Tuning Block Size and File Size
- ⁿ Tuning the LINUX Buffer Cache Size
- ⁿ Using Trace and Alert Files

The Importance of Tuning

Oracle8 is a highly optimizable software product. Frequent tuning optimizes system performance and prevents data bottlenecks. Although this chapter is written from the perspective of single-processor systems, most of the performance tuning tips provided here are also valid when using the Oracle parallel options.

Before Tuning the System

Before tuning the system, observe its normal behavior using the LINUX tools described in "LINUX Tools" in the next section.

See Also: Oracle8 Parallel Server Concepts and Administration. Oracle8 Tuning.

LINUX Tools

LINUX provides performance monitoring tools that can be used to assess database performance and determine database requirements.

In addition to providing statistics for oracle processes, these tools provide statistics for CPU usage, interrupts, swapping, paging, and context switching for the entire system.

See Also: LINUX tools are described in the operating system documentation.

vmstat

The vmstat utility reports process, virtual memory, disk, paging, and CPU activity on LINUX, depending on the switches you supply with the command. The following statement displays a summary of system activity eight times, at five second intervals:

```
% vmstat -n 5 8
```

Sample output from the vmstat command is shown in Figure 3–1.

The w column (under procs) shows the number of potential processes that have been swapped out (written to disk). If the value is not zero, swapping is occurring and your system has a memory shortage problem. The si and so columns indicate the number of swap-ins and swap-outs per second, respectively. Swap-outs should always be zero.

procs		memory	S	wap		io	sy	rstem			cpu
rbw swpd	free	buff cache	si	SO	bi	bo	in	CS	us	sy	id
0 0 0 16124	964	524 29904	2	14	13	21	208	3	9	4	87
1 0 0 16124	648	524 30140	0	0	1	0	806	1763	5	8	87
1 0 0 16124	608	524 29904	0	0	0	0	856	1894	5	7	87
0 0 0 16124	612	524 29624	0	0	0	5	734	1586	5	8	88
2 0 0 16124	1656	520 28296	0	0	221	0	687	1395	14	10	77
0 0 0 16124	840	520 29060	0	0	38	0	621	1287	3	4	93
0 0 0 16124	856	520 29196	0	0	0	0	647	1395	4	6	91
1 0 0 16124	708	520 29288	0	0	1	0	618	1287	3	4	93

Figure 3–1 Output from the vmstat -n command

free

The free utility reports information about swap space usage. A shortage of swap space can result in the system hanging and slow response time.

SQL Scripts

utlbstat and utlestat SQL Scripts

The utlbstat and utlestat SQL scripts are used to monitor Oracle database performance and tune the Shared Global Area (SGA) data structures. For information regarding these scripts, see the *Oracle8 Server Tuning*. On LINUX, the scripts are located in <code>\$ORACLE_HOME/rdbms/admin/</code>.

Tuning Memory Management

Start the memory tuning process by tuning paging and swapping space to determine how much memory is available.

The Oracle buffer manager ensures that the more frequently accessed data is cached longer. Monitoring the buffer manager and tuning the buffer cache can have a significant influence on Oracle performance. The optimal Oracle buffer size for your system depends on the overall system load and the relative priority of Oracle over other applications.

Allocate Sufficient Swap Space

Swapping causes significant LINUX overhead and should be minimized. Use free or vmstat -n on LINUX to check for swapping.

If your system is swapping and you need to conserve memory:

- avoid running unnecessary system daemon processes or application processes
- decrease the number of database buffers to free some memory
- ⁿ decrease the number of LINUX file buffers, especially if you are using raw devices

Procedures for adding swap space vary between LINUX implementations. On LINUX free to determine how much swap space is currently in use. Use free to add swap to your system. Consult your LINUX documentation for further information

Start with swap space two to four times your system's random access memory (RAM). a higher value if you plan to use CASE, Oracle Applications, or Oracle Office. Monitor use of swap space and increase it as necessary.

Control Paging

Paging may not present as serious a problem as swapping, because an entire program d not have to reside in memory in order to run. A small number of page-outs may not noticeably affect the performance of your system.

To detect excessive paging, run measurements during periods of fast response or idle ti compare against measurements from periods of slow response.

Use vmstat or free to monitor paging. The following columns are from the vmstat output are important:

- vflt/s indicates the number of address translation page faults. Address translation faults occur when a process references a valid page not in memory.
- rclm/s indicates the number of valid pages that have been reclaimed and added t free list by page-out activity. This value should be zero.

If your system consistently has excessive page-out activity, consider the following solu

- install more memory
- move some of the work to another system
- configure your kernel to use less memory

Hold the SGA in a Single Shared Memory Segment

Although this performance gain is minor, you cannot start the database without configure sufficient shared memory.

You may need to reconfigure the LINUX kernel to increase shared memory. The LINU kernel parameters for shared memory include SHMMAX, SHMMNI, and SHMSEG. In

order to ensure that the SGA resides in a single shared memory segment, set the value of SHMAX to 4294967295 (4 GB).

The size of the SGA can be estimated using the following steps:

- 1. Multiply DB_BLOCK_BUFFERS by DB_BLOCK_SIZE.
- **2.** Add the result of Step 1 to SORT_AREA_SIZE.
- **3.** Add the result of Step 2 to SHARED_POOL_SIZE.
- 4. Add the result of Step 3 to LOG_BUFFER.

You can also use the LINUX utility ipcs to monitor the status of shared memory.

See Also: "Configure LINUX Kernel for Oracle" in Chapter 2 of the *Oracle8 Installation Guide for LINUX*.

Tuning Disk I/O

I/O bottlenecks are the easiest performance problems to identify. Balance I/O evenly across all available disks to reduce disk access times. For smaller databases and those not using the Parallel Query option, ensure that different datafiles and tablespaces are distributed across the available disks.

Tune the Database Writer to Increase Write Bandwidth

Oracle offers solutions to prevent database writer (DBWR) activity from becoming a bottleneck:

- n use asynchronous I/O
- use I/O slaves

Asynchronous I/O

Asynchronous I/O allows processes to proceed with the next operation without having to wait after issuing a write and therefore improves system performance by minimizing idle time. Solaris supports Asynchronous I/O to both raw and filesystem datafiles.

I/O Slaves

I/O Slaves are specialized processes whose only function is to perform I/O. They are new with Oracle8, and replace Multiple DBWRs (in fact, they are a generalization of Multiple DBWRs and can be deployed by other processes as well), and can operate whether or not

asynchronous I/O is available. I/O Slaves come with a new set of initialization parameters which allow a degree of control over the way they operate. These are shown in Table 3–1.

Parameter	Range of Values	Default Value
DISK_ASYNCH_IO	TRUE/FALSE	TRUE
TAPE_ASYNCH_IO	TRUE/FALSE	TRUE
BACKUP_DISK_IO_SLAVES	TRUE/FALSE	FALSE
BACKUP_TAPE_IO_SLAVES	TRUE/FALSE	FALSE
DBWR_IO_SLAVES	0 - 999	0
LGWR_IO_SLAVES	0 - 999	0
ARCH_IO_SLAVES	0 - 999	0
DB_WRITER_PROCESSES	1-10	1

Table 3–1 Initialization Parameters for I/O Slaves

There may be times when the use of asynchronous I/O is not desirable or not possible. The first two parameters in Table 3–1, DISK_ASYNCH_IO and TAPE_ASYNCH_IO, allow asynchronous I/O to be switched off respectively for disk and tape devices. Because the number of I/O Slaves for each process type defaults to zero, no I/O Slaves will be deployed unless specifically set.

DBWR_IO_SLAVES should only be set to greater than 0 if ASYNC I/O (that is, DISK_ASYNCH_IO, or TAPE_ASYNCH_IO) has been disabled, otherwise DBWR will become a bottleneck. In this case the optimal value on LINUX for DBWR_IO_SLAVES should be 4. In the case of LGWR_IO_SLAVES, it is not recommended to deploy more than 9 slaves.

DB_WRITER_PROCESSES replaces the parameter DB_WRITERS, and specifies the initial number of database writer processes for an instance. If you use DBWR_IO_SLAVES, only one database writer process will be used, regardless of the setting for DB_WRITER_PROCESSES.

Monitoring Disk Performance

To monitor disk performance, use vmstat.

An important vmstat column for disk performance is %wio, the percentage of CPU time waiting on blocked I/O.

Key indicators are:
- The sum of bread, bwrit, pread and pwrit indicates the state of the disk I/O subsystem. The higher the sum, the greater the potential for disk I/O bottlenecks. The larger the number of physical drives, the higher the sum threshold number can be. A good default value is no more than 40 for two drives and no more than 60 for four to eight drives.
- ⁿ The %rcache should be greater than 90 and %wcache should be greater than 60. Otherwise, the system may be disk I/O bound.
- ⁿ If %wio is consistently greater than 20, the system is I/O bound.

Disk Performance Issues

Oracle block sizes should either match disk block sizes, or be a multiple of disk block sizes.

If possible, do a file system check on the partition before using it for database files, then make a new file system to ensure that it is clean and unfragmented. Distribute disk I/O as evenly as possible and separate log files from database files.

Tuning CPU Usage

Keep All Oracle Users/Processes at the Same Priority

Oracle is designed to operate with all users and background processes operating at the same priority level. Changing priorities causes unexpected effects on contention and response times.

For example, if the log writer process (LGWR) gets a low priority, it is not executed frequently enough and LGWR becomes a bottleneck. On the other hand, if LGWR has a high priority, user processes may suffer poor response time.

Use Processor Affinity/Binding on Multi-Processor Systems

In a multi-processor environment, use processor affinity/binding if it is available on your system. Processor binding prevents a process from migrating from one CPU to another, allowing the information in the CPU cache to be better utilized. You can bind a server shadow process to make use of the cache since it is always active, and let background processes flow between CPUs. Some platforms employ process binding automatically.

Use Single-Task Linking for Large Exports/Imports and SQL*Loader

Jobs

If you need to transfer large amounts of data between the user and Oracle8 (for example, using export/import), it is efficient to use single-task architecture. To make the single-task import (impst), export (expst), and SQL*Loader (sqlldrst) executables, use the ins_rdbms.mk makefile, which can be found in the \$ORACLE_HOME/rdbms/lib directory.

The following example makes the impst, expst, and sqlldrst executables:

```
% cd $ORACLE_HOME/rdbms/lib
```

% make -f ins_rdbms.mk expst impst sqlldrst

Note: Linking Oracle executables as a single-task allows a user process to directly accesses the entire SGA. In addition, running single-task requires more memory because the oracle executable text is no longer shared between the front-end and background processes.

Tuning Oracle Resource Contention

Tune LINUX Kernel Parameters

You can improve performance by keeping the LINUX kernel as small as possible. The LINUX kernel typically pre-allocates physical RAM, leaving less memory available for other processes, such as oracle.

Traditionally, kernel parameters such as NBUF, NFILE, and NOFILES were used to adjust kernel size. However, most LINUX implementations dynamically adjust those parameters at run time, even though they are present in the LINUX configuration file.

Look for memory mapped video drivers, networking drivers, and disk drivers. They can often be de-installed, yielding more memory for use by other processes.

WARNING: Remember to make a backup copy of your LINUX kernel. See your hardware vendor documentation for additional details.

Tuning Block Size and File Size

WARNING: To change block size, you must create a new database. Experiment with block size before transferring your data to the new database, to determine the most efficient configuration.

Specifying Oracle Block Size

On LINUX, the default Oracle block size is 2KB and the maximum block size is 16KB.

You can set the actual block size to any multiple of 2KB up to 16KB, inclusive.

The optimal block size is typically the default, but varies with the applications. To create a database with a different Oracle block size, add the following line to the initsid.ora file:

db_block_size=new_block_size

Tuning the LINUX Buffer Cache Size

To take full advantage of raw devices, adjust the size of the Oracle8 buffer cache and, if memory is limited, the LINUX buffer cache.

The LINUX buffer cache is provided by the operating system. It holds blocks of data in memory while they are being transferred from memory to disk, or vice versa.

The Oracle8 buffer cache is the area in memory that stores the Oracle database buffers. Since Oracle8 can use raw devices, it does not need to use the LINUX buffer cache.

When moving to raw devices, increase the size of the Oracle8 buffer cache. If the amount of memory on the system is limited, make a corresponding decrease in the LINUX buffer cache size.

The LINUX command vmstat may help you determine which buffer caches should be increased or decreased.

Adjusting Cache Size

- ⁿ Increase Oracle8 cache size as long as the cache hit ratio goes up.
- ⁿ Decrease cache sizes if the swapping/paging activity becomes high.

Using Trace and Alert Files

This section describes the trace (or dump) and alert files the Oracle Server creates to diagnose and resolve operating problems.

Trace File Names

The format of a trace file name is *processname_sid_pid*.trc, where:

	-
processname	is a three- or four-character process name showing which Oracle8 process the trace file is from (for example, PMON, DBWR, ORA, or RECO)
sid	is the instance system identifier
pid	is the LINUX process ID number
.trc	is a file name extension appended to all trace file names

Table 3–2 Format Key to Process Name

A sample trace file name is lgwr_TEST_1237.trc.

Alert Files

The alert_*sid*.log file is associated with a database and is located in the directory specified by the init*sid*.ora parameter BACKGROUND_DUMP_DEST. The default value is \$ORACLE_HOME/rdbms/log.

4

Administering SQL*Plus on Linux

- ⁿ Administering SQL*Plus
- ⁿ Using SQL*Plus
- n Restrictions

Administering SQL*Plus

Setup Files

The setup files for SQL*Plus are glogin.sql, the global setup file which defines the site profile, and login.sql, which defines the user profile. The glogin.sql and login.sql files contain either SQL statements or SQL*Plus commands that you choose to execute at the beginning of each SQL*Plus session. When you invoke SQL*Plus, glogin.sql is read first, followed by login.sql.

The Site Profile

The Site Profile file is \$ORACLE_HOME/sqlplus/admin/glogin.sql. SQL*Plus executes this command file whenever any user starts SQL*Plus and SQL*Plus establishes the Oracle connection. The default Site Profile is placed in \$ORACLE_HOME/sqlplus/admin whenever SQL*Plus is installed. If a Site Profile already exists, it will be overwritten. An existing Site Profile is deleted whenever SQL*Plus is de-installed.

The User Profile

The User Profile file is login.sql. SQL*Plus attempts to execute this command file whenever any user starts SQL*Plus and SQL*Plus establishes the Oracle connection. The User Profile is run after the Site Profile. SQL*Plus always searches the current directory for the User Profile. The environment variable SQLPATH may be set to a colon-separated list of directories that SQL*Plus will search in order.

For example, if the current directory is /u02/oracle and SQLPATH is set as follows:

% echo \$SQLPATH
/home:/home/oracle:/u01/oracle

SQL*Plus will first look for login.sql in the current directory /u02/oracle. If it is not found there, SQL*Plus will then look in /home, /home/oracle, and /u01/oracle, respectively.

Here is a sample login.sql file: set echo off set feedback 4 set pause on set pause "PLEASE PRESS RETURN TO CONTINUE" set message on set echo on

The PRODUCT_USER_PROFILE Table

The SQL script \$ORACLE_HOME/sqlplus/admin/pupbld.sql may be run as the user SYSTEM to create the Product and User Profile tables.

\$ORACLE_HOME/sqlplus/admin/pupbld.sql may also be run using the shell script \$ORACLE_HOME/bin/pupbld. To use this script, the environment variables ORACLE_HOME and SYSTEM_PASS must be set. SYSTEM_PASS must be set to the SYSTEM's username and password. For example:

```
% setenv SYSTEM_PASS SYSTEM/manager
% pupbld
```

Installing product user profile tables...

Product user profile tables installed.

pupbld.sql will only be run by the Installer during SQL*Plus installation if Create Database Objects was selected.

Demonstration Tables

SQL*Plus is shipped with demonstration tables that may be used for testing.

Default Install

If using Default Install and Create Database Objects, the user SCOTT and the demonstration tables will be created automatically.

Custom Install

When installing SQL*Plus using Custom Install, if Create Database Objects is selected and you answer 'Yes' to the prompt "Would you like to load the SQL*Plus Demo Tables?", the Installer will create the user SCOTT with the password TIGER and create the demonstration tables.

Creating Demonstration Tables Manually

The SQL script \$ORACLE_HOME/sqlplus/demo/demobld.sql is used to create the demonstration tables. The file demobld.sql, may be run in SQL*Plus as any user to create the demonstration tables in that schema. For example:

```
% sqlplus scott/tiger
SQL> @?/sqlplus/demo/demobld.sql
```

\$ORACLE_HOME/sqlplus/demo/demobld.sql may also be run using the shell script \$ORACLE_HOME/bin/demobld as follows:

```
% demobld scott tiger
```

Deleting Demonstration Tables

The SQL script \$ORACLE_HOME/sqlplus/demo/demodrop.sql is used to drop the demonstration tables. The file demodrop.sql may be run in SQL*Plus as any user to drop the demonstration tables from that user's schema. For example:

```
% sqlplus scott/tiger
SQL> @?/sqlplus/demo/demodrop.sql
```

\$ORACLE_HOME/sqlplus/demo/demodrop.sql may also be run using the shell script \$ORACLE_HOME/bin/demodrop as follows:

```
% demodrop scott tiger
```

Note: Both SQL scripts demobld.sql and demodrop.sql drop the tables EMP, DEPT, BONUS, SALGRADE, and DUMMY. You must ensure that a table does not exist with the same name in the desired schema prior to running either script or the table data will be lost.

Help Facility

Default Install

If using Default Install and Create Database Objects, the Help Facility is installed automatically.

Custom Install

When installing SQL*Plus, if Create Database Objects is selected and you answer 'Yes' to the prompt "Would you like to load the SQL*Plus Help Facility?", the Installer will create the Help Facility.

Installing the Help Facility Manually

The Help Facility may be installed manually using the shell script \$ORACLE_HOME/bin/helpins. To use this script, the environment variables ORACLE_HOME and SYSTEM_PASS must be set. SYSTEM_PASS must be set to SYSTEM's username and password. For example:

```
$ setenv SYSTEM_PASS SYSTEM/manager
$ helpins
SOL*Loader: Release 8.0.5.0.0 - Production
(c) Copyright 1998 Oracle Corporation. All rights reserved.
Commit point reached - logical record count 828
SQL*Loader: Release 8.0.5.0.0 - Production
(c) Copyright 1998 Oracle Corporation. All rights reserved.
Commit point reached - logical record count 1024
Commit point reached - logical record count 1207
SOL*Loader: Release 8.0.5.0.0 - Production
(c) Copyright 1998 Oracle Corporation. All rights reserved.
Commit point reached - logical record count 1024
Commit point reached - logical record count 1304
Commit point reached - logical record count 2328
Commit point reached - logical record count 2724
Commit point reached - logical record count 2835
```

See Also: Refer to the *SQL*Plus User's Guide and Reference*, and the README file, \$ORACLE_HOME/sqlplus/doc/release.doc.

Using SQL*Plus

Using a System Editor from SQL*Plus

An ed or edit command entered at the SQL*Plus prompt calls a default operating system editor, such as ed, emacs, ned, or vi. Your PATH variable must include the directory of the editor.

The global default editor is usually set by the DBA in glogin.sql using the SQL*Plus __editor option. Override this setting by specifying an editor in login.sql. Both files are read by SQL*Plus at startup, the local file taking precedence. The __editor option can also be set during a SQL*Plus session, overriding the setting in either file.

If the __editor option is not set, the EDITOR and VISUAL environment variables specify the SQL*Plus editor. These variables are not set in glogin.sql or login.sql. They are set in a user startup file, or at the system prompt. If both are set, the EDITOR variable is used.

Setting the Order of the Editor

SQL*Plus searches for the default editor in this order:

- 1. The _editor variable during a SQL*Plus session.
- 2. The _editor variable in login.sql.
- 3. The _editor variable in glogin.sql.
- 4. The EDITOR environment variable.
- 5. The VISUAL environment variable.

When none of these values are set, SQL*Plus uses ed.

Setting the _editor option

Set the SQL*Plus _editor option by adding the following line to the login.sql file:

define _editor=editor_name

where *editor_name* is a LINUX editor.

Setting Environment Variables

For the Bourne or Korn shell, set the default editor with an environment variable by entering:

\$ LINUX_VAR=editor_name; export LINUX_VAR

For the C shell, set the default editor with an environment variable by entering:

% setenv LINUX_VAR editor_name

Environment variable syntax is explained in Table 4–1.

Table 4–1 Syntax for LINUX Environment Variables

LINUX_VAR	the EDITOR or VISUAL environment variable
editor_name	the LINUX editor (for example, vi or ed)

Default Settings

If you call the system editor, the current SQL buffer is placed in the edit buffer and all statements available to the editor can change the SQL statement. SQL*Plus uses the afiedt.buf temporary file. When you exit the editor, the changed SQL buffer is returned to SQL*Plus.

Running Operating System Commands from SQL*Plus

An exclamation point (!) in the first position after the SQL*Plus prompt indicates subsequent character strings are passed to a sub-shell. The SHELL environment variable selects the shell you use to execute operating system commands. The default shell is /bin/sh (sh). If the shell cannot be executed, an error message is displayed.

Use the following SQL*Plus commands to perform specific tasks:

- ⁿ Enter [!]+[*command*] to execute one operating system command. After the command executes, control returns to SQL*Plus.
- ⁿ Enter [!]+[Return] to execute *more than one* operating system command. When you finish, enter [Ctrl]+[d] to return to SQL*Plus.

Interrupting SQL*Plus

While running SQL*Plus:

- ⁿ You can stop the scrolling record display and terminate a SQL statement by pressing [Ctrl]+[c] on BSD machines or [Delete] on System V machines.
- ⁿ If you are at the SQL*Plus prompt, pressing [Interrupt] displays another SQL*Plus prompt.

Using the SPOOL Command

The default filename extension for files generated by the SPOOL command is .lst. To change the extension, specify a spool file containing a period (.).

For example:

SQL> SPOOL query.lis

Restrictions

COPY Command

The COPY command in SQL*Plus is supported without restrictions on different machines running the same version of the operating system.

COPY may also work between machines running different versions of the operating system. If COPY fails, test the connection using rcp or ftp. Restrictions in vendor-supplied networking software may prevent rcp, ftp, or COPY from functioning properly between systems.

Note: The rlogin command does not send or receive large packets of data and is not an adequate test for connections.

If COPY does not function between systems, create a database link to the system and user ID indicating the table you want to copy. To do this, enter:

SQL> create table newtable as \
(SELECT * FROM table@database_link_name)

This selects the rows and columns from the original table on the remote system and enters them in the new table on the local system.

Resizing Windows

The default value for SQL*Plus LINESIZE is 80 and for PAGESIZE is 25. These variables do not automatically adjust for window size.

Return Codes

LINUX return codes use only one byte, which is not enough space to return an Oracle error code. The range for a return code is 0 to 255.

5

Using Oracle Precompilers and the Oracle Call Interface on Linux

- ⁿ Overview of Oracle Precompilers
- n Pro*C/C++
- ⁿ Oracle Call Interface
- ⁿ Oracle Precompiler and Oracle Call Interface Linking and Makefiles
- ⁿ Thread Support
- ⁿ Static and Dynamic Linking with Oracle Libraries
- ⁿ Using Signal Handlers
- n XA Functionality

Overview of Oracle Precompilers

Oracle precompilers are application design tools used to combine SQL statements from an Oracle database with programs written in a high-level language. Oracle precompilers are compatible with ANSI SQL and are used to develop open, customized applications that run with Oracle8, or any other ANSI SQL DBMS.

Relinking Precompiler Executables

All precompiler executables are relinked using the makefile,

\$ORACLE_HOME/precomp/lib/ins_precomp.mk. The make command uses the
following convention:

\$ make -f ins_precomp.mk relink EXENAME=executable

This command will create the new executable in the \$ORACLE_HOME/precomp/lib directory, and then move it to \$ORACLE_HOME/bin. In order to create the new executable without it being moved to \$ORACLE_HOME/bin, use the following command:

\$ make -f ins_precomp.mk executable

where the name of the executable in respect of the product being used, can be determined from Table 5-1.

Table 5–1 Products and Their Corresponding Executable Names

Product	Executable
Pro*C/C++	proc
Object Type Translator	ott

For example, to relink the Pro*C/C++ executable, use the following command:

\$ cd \$ORACLE_HOME/precomp/lib

\$ make -f ins_precomp.mk relink EXENAME=proc

Precompiler Configuration Files

There are six .cfg system configuration files in \$ORACLE_HOME/precomp/admin. These are described in Table 5–2.

Table 5–2 System Configuration Files

Product	Configuration File
Pro*C/C++ v8.0.5	pcscfg.cfg
Object Type Translator v8.0.5	ottcfg.cfg

Issues Common to All Precompilers

Uppercase to Lowercase Conversion

In languages other than C, your compiler converts an uppercase function or subprogram name to lowercase. This can cause "No such user exit" errors. In this case, verify that the function or subprogram name in your option file matches the case in the iapxtb table.

Vendor Debugger Programs

Precompilers and vendor-supplied debuggers may be incompatible. Oracle Corporation does not guarantee that a program run under a debugger will run the same way under an operating system.

Value of ireclen and oreclen

The ireclen and oreclen parameters do not have maximum values.

Supplemental Documentation

The following documents provide additional information about precompiler and interface features:

- ⁿ *Programmer's Guide to the* Pro*C/C++ *Precompiler*
- ⁿ *Programmer's Guide to the Oracle Call Interface*
- ⁿ Oracle8 Server Application Developer's Guide

Pro*C/C++

For additional information regarding Pro*C/C++ release 8.0.5, see the README file, \$ORACLE_HOME/precomp/doc/proc2/readme.doc.

Administering Pro*C/C++

System Configuration File

The system configuration file for Pro*C/C++ is \$ORACLE_HOME/precomp/admin/pcscfg.cfg.

Using Pro*C/C++

Prior to using Pro*C/C++, verify that the correct version of the Operating System compiler is properly installed. The required version is documented in Chapter 1 of the *Oracle8 Installation Guide for LINUX*.

Demonstration Programs

Demonstration programs are provided to show the various functionality of the Pro*C/C++ precompiler. There are three types of demonstration programs: C, C++, and Object programs - the latter demonstrate the new Oracle8 Object features. All the demonstration programs are located in \$ORACLE_HOME/precomp/demo/proc, and all of them assume that the demonstration tables created by \$ORACLE_HOME/sqlplus/demo/demobld.sql exist in the SCOTT schema with the password TIGER.

For further information on building the demonstration programs using SQL*Plus, see "Demonstration Tables" on page 4-3 of this book. For further information on the demonstration programs see the *Programmer's Guide to the* Pro*C/C++ *Precompiler*.

The makefile, <code>\$ORACLE_HOME/precomp/demo/proc/demo_proc.mk</code>, should be used to create the demonstration programs. For example, to precompile, compile, and link the <code>sample1</code> demonstration program, enter the following command.

\$ make -f demo_proc.mk sample1

Alternatively, the following command may be used, which achieves exactly the same result, only with more explicit syntax.

\$ make -f demo_proc.mk build OBJS=sample1.o EXE=sample1

By default, all programs are dynamically linked with the client shared library, \$ORACLE_HOME/lib/libclntsh.so. To create all Pro*C/C++ C demonstration programs, enter the following command:

\$ make -f demo_proc.mk samples

To create all Pro*C/C++ C++ demonstration programs, enter this command:

\$ make -f demo_proc.mk cppsamples

To create all Pro*C/C++ Object demonstration programs, enter this command:

\$ make -f demo_proc.mk object_samples

Some demonstration programs require a SQL script, found in \$ORACLE_HOME/precomp/demo/sql, to be run. In order to build such a demonstration program and run the corresponding SQL script, the make macro argument, RUNSQL=run, must be included on the command line. For example, to create the calldemo demonstration program and run the required \$ORACLE_HOME/precomp/demo/sql/calldemo.sql script, use the following command syntax:

\$ make -f demo_proc.mk calldemo RUNSQL=run

As another example, to create all Object demonstration programs and run all corresponding required SQL scripts, enter the following command:

\$ make -f demo_proc.mk object_samples RUNSQL=run

The SQL scripts may also be run manually, if desired.

User Programs

The makefile, \$ORACLE_HOME/precomp/demo/proc/demo_proc.mk, may be used to create user programs. The general syntax for linking a user program with demo_proc.mk is as follows:

\$ make -f demo_proc.mk target OBJS="objfile1 objfile2 ..." \
EXE=exename

For example, to create the program, myprog, from the Pro*C/C++ source myprog.pc, use one of the following commands, depending on the source and type of executable desired:

For C source, dynamically linked with client shared library:

\$ make -f demo_proc.mk build OBJS=myprog.o EXE=myprog

For C source, statically linked:

\$ make -f demo_proc.mk build_static OBJS=myprog.o EXE=myprog

For C++ source, dynamically linked with client shared library:

\$ make -f demo_proc.mk cppbuild OBJS=myprog.o EXE=myprog

For C++ source, statically linked:

\$ make -f demo_proc.mk cppbuild_static OBJS=myprog.o EXE=myprog

For LINUX issues on the use of shared libraries, refer to the LINUX documentation.

Oracle Call Interface

Using the Oracle Call Interface

Prior to using the Oracle Call interface (OCI), verify that the correct version of the compiler is properly installed. The required version for your operating system is specified in Chapter 1 of the *Oracle8 Installation Guide for LINUX*.

Demonstration Programs

Demonstration programs have been provided that show various functionality of the OCI. There are two types of demonstration programs: C and C++. All the demonstration programs are located in \$ORACLE_HOME/rdbms/demo. Many of the demonstration programs assume that the demonstration tables created by \$ORACLE_HOME/sqlplus/demo/demobld.sql exist in the SCOTT schema with the password TIGER.

For further information on building the demonstration programs using SQL*Plus, see "Demonstration Tables" on page 4-3 of this book.

See Also: For further information on the demonstration programs see the *Programmer's Guide to the Oracle Call Interface* and the program source for details of each program.

The makefile, \$ORACLE_HOME/rdbms/demo_rdbms.mk, should be used to create the demonstration programs. For example, to compile and link the cdemo1 demonstration program, enter the following command:

\$ make -f demo_rdbms.mk cdemo1

Alternatively, the following command may be used, which achieves exactly the same result, only with more explicit syntax:

\$ make -f demo_rdbms.mk build OBJS=cdemo1.o EXE=cdemo1

By default, all programs are dynamically linked with the client shared library, \$ORACLE_HOME/lib/libclntsh.so.

To create all OCI C demonstration programs, enter the following command:

\$ make -f demo_rdbms.mk demos

To create all OCI C++ demonstration programs, enter this command:

\$ make -f demo_rdbms.mk c++demos

Note: If you receive the following errors while linking a C++ program:

ld: fatal: library -lsunmath: not found ld: fatal: library -lC: not found ld: fatal: library -lC_mtstubs: not found ld: fatal: library -lcx: not found

it will be necessary to include in LD_LIBRARY_PATH, the directory in which the specified libraries exist.

Some demonstration programs require a SQL script, located in \$ORACLE_HOME/rdbms/demo, to be run manually prior to executing the program. In most cases, the SQL script name is the same as the program name with a .sql extension. For example, the SQL script for the program oci02 is oci02.sql.

Read the comments at the beginning of the program to determine the required SQL script, if any.

User Programs

The makefile, \$ORACLE_HOME/rdbms/demo/demo_rdbms.mk, may be used to create user programs. The general syntax for linking a user program with demo_rdbms.mk is:

\$ make -f demo_rdbms.mk target OBJS="objfile1 objfile2 ..." \
EXE=exename

For example, to create the program myprog from the C source myprog.c, use one of the following commands depending on the type of executable desired:

For C source, dynamically linked with client shared library:

\$ make -f demo_rdbms.mk build OBJS=myprog.o EXE=myprog

For C source, statically linked:

\$ make -f demo_rdbms.mk build_static OBJS=myprog.o EXE=myprog

To create the program myprog from the C++ source myprog.cc

For C++ source, dynamically linked with client shared library:

\$ make -f demo_rdbms.mk buildc++ OBJS=myprog.o EXE=myprog

For C++ source, statically linked:

\$ make -f demo_rdbms.mk buildc++_static OBJS=myprog.o EXE=myprog

Oracle Precompiler and Oracle Call Interface Linking and Makefiles

Custom Makefiles

It is recommended that the provided demo_product.mk makefiles be used to link user programs as described in the specific product sections of this chapter. If it is necessary to modify the provided makefile, or if you decide to use a custom written makefile, the following should be noted:

Do not modify the ordering of the Oracle libraries.
 Oracle libraries are included on the link line more than once so all symbols will be resolved during linking. There are two reasons for this:

- 1. Oracle libraries are mutually referential, meaning that functions in library A call functions in library B, and functions in library B call functions in library A.
- **2.** The Solaris linker is a one-pass linker, meaning that the linker will search a library exactly once at the point it is encountered in the link line.
- If you add your own library to the link line, it should be added to the beginning or to the end of the link line.
 User libraries should not be placed between the Oracle libraries.
- Oracle library names and the contents of those libraries are subject to change between releases. Always use the ddemo_product.mk makefile that ships with the current release as a guide to determine which libraries are necessary.

Undefined Symbols

A common error when linking a program is undefined symbols, similar to the following:

```
$ make -f demo_proc.mk sample1
Undefined first referenced
symbol in file
sqlcex sample1.o
sqlglm sample1.o
ld: fatal: Symbol referencing errors. No output written to sample1
```

This error occurs when the linker cannot find a definition for a referenced symbol. Generally, the remedy for this type of problem is to ensure that the library or object file containing the definition exists on the link line and that the linker is searching the correct directories for the file.

Oracle provides a utility called symfind to assist in locating a library or object file where a symbol is defined. Here is example output of symfind locating the symbol sqlcex:

\$ symfind sqlcex

SymFind - Find Symbol <sqlcex> in <**>.a, .o, .so _____ Command: /u01/app/oracle/product/8.0.5/bin/symfind sqlcex Local Directory: /u01/app/oracle/product/8.0.5 Output File: (none) Note: I do not traverse symbolic links Use '-v' option to show any symbolic links Locating Archive and Object files ... [11645] | 467572 | 44 FUNC |GLOB |0 |8 sqlcex ./lib/libclntsh.so 0 | 44 | FUNC | GLOB | 0 | 5 | sqlcex [35] ./lib/libsql.a

Thread Support

The Oracle libraries provided with this release are thread safe, allowing support for multi-threaded applications.

Static and Dynamic Linking with Oracle Libraries

Precompiler and OCI applications can be linked with Oracle Libraries either statically or dynamically. With static linking, the libraries and objects of the whole application are

linked together into a single executable program. As a result, application executables can become fairly large.

With dynamic linking, the executing code partly resides in the executable program, and also resides in libraries that are linked by the application dynamically at run-time. Libraries that are linked at run-time are called dynamic or shared libraries. There are two primary benefits of dynamic linking:

1. Smaller disk requirements:

Different applications, or different invocations of the same application, can use the same shared or dynamic library. As a result, the overall disk requirements are reduced.

2. Smaller main memory requirements:

The same shared or dynamic library image (i.e., the in-memory copy), can be shared by different applications. This means that a library needs to be loaded only once into the main memory and then multiple applications can use the same library. As a result, main memory requirements are reduced.

Oracle Shared Library

The Oracle shared library is <code>\$ORACLE_HOME/lib/libclntsh.so</code>. If the Oracle provided demo_*product*.mk makefile is used to link an application, the Oracle shared library is used by default.

It may be necessary to set the environment variable LD_LIBRARY_PATH so the runtime loader can find the Oracle shared library at process start-up. If you receive the following error when starting an executable, LD_LIBRARY_PATH must be set to the directory where the Oracle shared library exists:

```
% sample1
ld.so.1: sample1: fatal: libclntsh.so.1.0: can't open file: errno=2
Killed
```

Set LD_LIBRARY_PATH as follows:

% setenv LD_LIBRARY_PATH \$ORACLE_HOME/lib

The Oracle shared library is created automatically during installation. If there is a need to recreate the Oracle shared library, exit **all** client applications using the Oracle shared library, including all Oracle client applications like SQL*Plus and Recovery Manager, and run the following command logged in as the *oracle* user:

```
% cd $ORACLE_HOME/rdbms/lib
% make -f ins_rdbms.mk client_sharedlib
```

Using Signal Handlers

This section describes signals Oracle8 uses for two-task communication, and explains how to set up your own signal handlers.

Signals

Signals are installed in a user process when you connect to the database, and are de-installed when you disconnect.

Oracle8 uses the following signals for two-task communications:

SIGCONT	used by the pipe two-task driver to send out-of-band breaks from the user process to the oracle process.
SIGINT	used by all two-task drivers to detect user interrupt requests. SIGINT is not caught by oracle; it is caught by the user process.
SIGPIPE	used by the pipe driver to detect end-of-file on the communications channel. When writing to the pipe, if no reading process exists, a SIGPIPE signal is sent to the writing process. SIGPIPE is caught by both the oracle process and the user process.
SIGCLD	used by the pipe driver. SIGCLD is similar to SIGPIPE, but only applies to user processes, not oracle processes. When an oracle process dies, the LINUX kernel sends a SIGCLD to the user process (wait () is used in the signal handler to see if the server process died). SIGCLD is not caught by oracle; it is caught by the user process.
SIGTERM	used by the pipe driver to signal interrupts from the user side to the oracle process. This occurs when the user presses the interrupt key [Ctrl]+[c]. SIGTERM is not caught by the user process; it is caught by oracle.
SIGIO	used by Oracle Net8 protocol adapters to indicate incoming networking events.
SIGURG	used by the Oracle Net8 TCP/IP drivers to send out-of-band breaks from the user process to the oracle process.

Table 5–3 Signals for Two-Task Communications

The listed signals affect Pro*C or other precompiler applications. You can install one signal handler for SIGCLD (or SIGCHLD) and SIGPIPE when connected to the oracle process. You can have multiple signal handlers for SIGINT as long as the osnsui() routine is called to set this up. You can install as many signal handlers as you want for other signals. If you are not connected to the oracle process, you can have multiple signal handlers.

Sample Signal Routine

The following example shows how you can set up your own signal routine and the catching routine. For SIGINT, use osnsui() and osncui() to register and delete signal-catching routines.

```
/* user side interrupt set */
word osnsui( /*_ word *handlp, void (*astp), char * ctx, _*/)
/*
** osnsui: Operating System dependent Network Set
**User-side
** Interrupt. Add an interrupt handling procedure
**astp.
```

```
** Whenever a user interrupt(such as a ^C) occurs,
**call astp
** with argument ctx. Put in *handlp handle for this
**handler so that it may be cleared with osncui.
** Note that there may be many handlers; each should
** be cleared using osncui. An error code is
**returned if an error occurs.
*/
/* user side interrupt clear */
word osncui( /*_ word handle _*/ );
/*
** osncui: Operating System dependent Clear User-side
**Interrupt.
** Clear the specified handler. The argument is the
**handle obtained from osnsui. An error code is
** returned if an error occurs.
*/
```

The following is a template for using osnsui() and osncui() in an application program:

```
/*
** My own user interrupt handler.
*/
void sig_handler()
{
. . .
}
main(argc, argv)
int arc;
char **argv;
   ł
   int handle, err;
   . . .
   /* set up my user interrupt handler */
   if (err = osnsui(&handle, sig handler, (char *) 0))
      ł
      /* if the return value is non-zero, an error has occurred
      Do something appropriate here. */
      . . .
      }
```

```
...
/* clear my interrupt handler */
if (err = osncui(handle))
{
    /* if the return value is non-zero, an error has occurred
    Do something appropriate here. */
...
}
...
}
```

XA Functionality

When building a TP-monitor XA application, ensure that the TP-monitors libraries (that define the symbols ax_reg and ax_unreg) are placed in the link line before Oracle's client shared library. This link restriction is required only when using XA's dynamic registration (Oracle XA switch xaoswd).

The Oracle8 Server does not support Oracle7 7.1.6 XA calls (although it does support 7.3 XA calls), hence TP-monitor XA applications using 7.1.6 XA calls must be relinked with the Oracle8 XA library. The Oracle8 XA calls are defined in both the shared library \$ORACLE_HOME/lib/libclntsh.so and the static library \$ORACLE_HOME/lib/libclient.a.

<u>6</u>

Configuring Oracle Net8

- ⁿ Supplemental Documentation
- ⁿ Core Net8 Products and Features
- ⁿ Oracle Net8 Protocol Adapters
- ⁿ The BEQ Protocol Adapter
- ⁿ The IPC Protocol Adapter
- ⁿ The TCP/IP Protocol Adapter
- ⁿ Net8 Naming Adapters
- ⁿ Oracle Enterprise Manager (OEM) Intelligent Agent

Supplemental Documentation

See Also: The following documents provide a full discussion of Oracle Net8 features:

- Oracle Net8 Administrator's Guide
- ⁿ Oracle Networking Quick Reference Card for Net8
- n Oracle Security Server Guide
- ⁿ Oracle Cryptographic Toolkit Programmer's Guide

Supplementary Information in README Files

n

Table 6–1 shows the location of README files for various bundled products. The README files describe changes since the last release.

Table 6–1 Location of README Files for Oracle Products

Product	README File
Net8	<pre>\$ORACLE_HOME/network/doc/README.Net8</pre>
Oracle Intelligent Agent	<pre>\$ORACLE_HOME/network/doc/README.oemagent</pre>
Oracle Security Server	<pre>\$ORACLE_HOME/network/doc/README.OSS</pre>
Oracle Names Server	<pre>\$ORACLE_HOME/network/install/names/doc/README.doc</pre>
Oracle TCP/IP Protocol Adapter	<pre>\$ORACLE_HOME/network/install/tcppa/doc/README.doc</pre>

Core Net8 Products and Features

See Also: Sample files can be found in the *Oracle Net8 Administrator's Guide*.

Net8 Files and Utilities

Location of Net8 Configuration Files

The default directory for global Oracle Net8 and Connection Manager files is /var/opt/oracle on LINUX.

Oracle Net8 and Connection Manager search for global files in the following order:

- 1. The directory specified by the environment variable, TNS_ADMIN, if set.
- 2. The /var/opt/oracle directory.
- 3. \$ORACLE_HOME/network/admin.

If your files are not in the default directory, use the TNS_ADMIN environment variable in the startup files of all network users to specify a different location:

For the C shell, enter:

% setenv TNS_ADMIN new_default

For each system level configuration file, users may have a corresponding local private configuration file (stored in the user's home directory). The settings in the private file override the settings in the system level file. The private configuration file for sqlnet.ora is \$HOME/.sqlnet.ora. The private configuration file for tnsnames.ora is \$HOME/.tnsnames.ora. Syntax for these files is identical to that of the corresponding system files.

Sample Configuration Files

Examples of the cman.ora, listner.ora, names.ora, sqlnet.ora, and tnsnames.ora configuration files are located in \$ORACLE_HOME/network/admin/samples.

The adapters Utility

To display installed Oracle Net8 adapters, enter:

% adapters

To display adapters linked with a specific executable, enter:

% adapters executable

For example, the following command displays the adapters linked with the oracle executable:

% adapters oracle Protocol Adapters linked with oracle are: BEQ Protocol Adapter IPC Protocol Adapter TCP/IP Protocol Adapter Net8 Naming Adapters linked with oracle are: Oracle TNS Naming Adapter Oracle Naming Adapter Advanced Networking Option/Network Security products linked with oracle are: Oracle Security Server Authentication Adapter

Oracle Connection Manager

For information on the Oracle Connection Manager see the Net8 Administrator's Guide.

Multi-Threaded Server

For information on the Multi-Threaded Server see the *Oracle8 Server Concepts* and *Oracle8 Administrator's Guide*.

Oracle Names

For information on Oracle Names see the Oracle Net8 Administrator's Guide.

Oracle Net8 Protocol Adapters

The supported Protocol Adapters for Net8 version 8.0.5 on LINUX are BEQ Protocol Adapter, IPC Protocol Adapter, TCP/IP Protocol Adapter.

Prior to installing the TCP/IP Net8 Protocol Adapters, the appropriate operating system software must be installed and configured. Refer to the *Oracle8 Installation Guide for LINUX* for requirements details. The BEQ and IPC Net8 Protocol Adapters do not have any specific operating system requirement.

The IPC, TCP/IP Net8 Protocol Adapters each have a protocol-specific ADDRESS specification that is used for Net8 configuration files and for the MTS_LISTENER_ADDRESS database initialization parameter (init.ora). See the ADDRESS specification heading under each Protocol Adapter section in this chapter for details.

Table 6–2 shows a summary of ADDRESS specifications for each Protocol Adapter.

Protocol Adapter	ADDRESS Specification
BEQ	<pre>(ADDRESS = (PROTOCOL = BEQ) (PROGRAM = ORACLE_HOME/bin/oracle) (ARGV0 = oracleORACLE_SID) (ARGS = '(DESCRIPTION=(LOCAL=YES)(ADDRESS=(PROTOCOL=BEQ)))') (ENVS = 'ORACLE_HOME=ORACLE_HOME,ORACLE_SID=ORACLE_SID'))</pre>
IPC	(ADDRESS = (PROTOCOL=IPC) (KEY= <i>key</i>))
TCP/IP	<pre>(ADDRESS = (PROTOCOL=TCP) (HOST=hostname) (PORT=port_id))</pre>

Table 6–2 ADDRESS Specification Summary

The BEQ Protocol Adapter

Overview of the BEQ Protocol Adapter

The BEQ Protocol Adapter, is both a communications mechanism and a process spawning mechanism. If a service name is not specified, either directly by the user on the command line or the login screen, or indirectly through an environment variable such as TWO_TASK, then the BEQ Protocol Adapter will be used. In which case, a dedicated server will always be used, and the multi-threaded server will never be used. This dedicated server is started automatically by the BEQ Protocol Adapter, which waits for the server process to start and attach to an existing SGA. If the startup of the server process is successful, the BEQ Protocol Adapter then provides inter-process communication via UNIX pipes.

An important feature of the BEQ Protocol Adapter is that no network Listener is required for its operation, since the adapter is linked into the client tools and directly starts its own server process with no outside interaction. However, the BEQ Protocol Adapter can only be used when the client program and the Oracle8 server reside on the same machine. The BEQ Protocol Adapter is always installed, and always linked in to all client tools and to the Oracle8 server.

Specifying a BEQ ADDRESS

The BEQ Protocol Adapter connection parameters are part of the ADDRESS keyword-value pair. You can enter the parameters in any order.

```
(ADDRESS =
    (PROTOCOL = BEQ)
    (PROGRAM = ORACLE_HOME/bin/oracle)
    (ARGV0 = oracleORACLE_SID)
    (ARGS = '(DESCRIPTION=(LOCAL=YES)(ADDRESS=(PROTOCOL=BEQ)))')
    (ENVS = 'ORACLE_HOME=ORACLE_HOME,ORACLE_SID=ORACLE_SID')
)
```

Syntax for BEQ Protocol Adapter connection parameters is described in Table 6–3.

Table 6–3 Syntax for BEQ Protocol Adapter Connection Parameters

PROTOCOL	Specifies the adapter to be used. The value is beq and may be specified in either uppercase or lowercase.
PROGRAM	The full path to the oracle executable.
ARGV0	The name of the process as it appears in a ps listing. The recommended value is oracleORACLE_SID.
ARGS	'(DESCRIPTION=(LOCAL=YES)(ADDRESS=(PROTOCOL=BEQ)))'
ENVS	Environment specification where ORACLE_HOME is the full path to the ORACLE_HOME directory of the database to connect, and ORACLE_SID is the system identifier of the database to connect.

Example 6–1 BEQ ADDRESS Specifying a Client

The following is an example of an BEQ ADDRESS:

```
(ADDRESS =
    (PROTOCOL = BEQ)
    (PROGRAM = /u01/app/oracle/product/8.0.5/bin/oracle)
    (ARGV0 = oracleV805)
    (ARGS = '(DESCRIPTION=(LOCAL=YES)(ADDRESS=(PROTOCOL=BEQ)))')
    (ENVS = 'ORACLE_HOME=/u01/app/oracle/product/8.0.5,ORACLE_SID=V805')
)
```

The ADDRESS is commonly part of a larger construct such as a connect descriptor or configuration file.

The IPC Protocol Adapter

Overview of the IPC Protocol Adapter

The IPC Protocol Adapter, is similar to the BEQ Protocol Adapter in that it can only be used when the client program and the Oracle8 server reside on the same machine. The IPC Protocol Adapter differs from the BEQ Protocol Adapter in that it can be used with dedicated server and multi-threaded server configurations. The IPC Protocol Adapter requires a network listener for its operation. The IPC Protocol Adapter is always installed, and always linked in to all client tools and to the Oracle8 server.

For the IPC Protocol Adapter, the location of the UNIX Domain Socket (IPC) file on LINUX systems changed after Oracle7 7.1. Thus, if you have Oracle7 7.1 installed on the same machine as Oracle8, and you attempt to make an IPC connection between the two instances, the connection may fail. The solution to this problem is to make a symbolic link between the directory where the IPC file used to be (/var/tmp/o) and where it now resides (/var/tmp/.oracle).

Specifying an IPC ADDRESS

The IPC Protocol Adapter connection parameters are part of the ADDRESS keyword-value pair. You can enter the parameters in any order.

```
(ADDRESS=
(PROTOCOL=IPC)
(KEY=key)
)
```

Syntax for IPC Protocol Adapter connection parameters is described in Table 6-4.

Table 6–4 Syntax for IPC Protocol Adapter Connection Parameters

PROTOCOL	Specifies the adapter to be used. The value is ipc and may be specified in either uppercase or lowercase.
KEY	Service name of database or database identifier (SID).

Example 6–2 IPC ADDRESS Specifying a Client

The following is an example of an IPC ADDRESS:

```
(ADDRESS=
(PROTOCOL=IPC)
(KEY=PROD)
```

The ADDRESS is commonly part of a larger construct such as a connect descriptor or configuration file.

The TCP/IP Protocol Adapter

Overview of the TCP/IP Protocol Adapter

Oracle Corporation recommends that you reserve a port for your Oracle Net8 listener in the /etc/services file of each node on the network that defines the Oracle Net8 listener port. The port is commonly 1521. The entry should list the listener name and the port number, for example:

listener 1521/tcp

where *listener* is the name of the listener, as defined in listener.ora.

Reserve more than one port to start more than one listener.

Specifying a TCP/IP ADDRESS

)

The TCP/IP Protocol Adapter connection parameters are part of the ADDRESS keyword-value pair. You can enter the three parameters in any order.

```
(ADDRESS=
   (PROTOCOL=TCP)
   (HOST=hostname)
   (PORT=port id)
```

Syntax for TCP/IP Protocol Adapter connection parameters is described in Table 6-5.

Table 6–5 Syntax for TCP/IP Protocol Adapter Connection Parameters

PROTOCOL	Specifies the adapter to be used. The value can be uppercase or lowercase. The default is tcp.
HOST	The host name or the host IP address.
PORT	The TCP/IP port. Either a number or the name specified in the /etc/services file. Oracle Corporation recommends a value of 1521.

Example 6–3 TCP/IP ADDRESS Specifying a Client

Following is an example of the TCP/IP ADDRESS specifying a client on the MADRID host:

```
(ADDRESS=
(PROTOCOL=TCP)
(HOST=MADRID)
(PORT=1521)
```

The last field could be specified by name, for example, (PORT=listener). The ADDRESS is commonly part of a larger construct such as a connect descriptor or configuration file.

Net8 Naming Adapters

NIS Naming Adapter

For details on configuring the NIS Naming Adapter, see the *Oracle Net8 Administrator's Guide*, Release 8.0.

Oracle Enterprise Manager (OEM) Intelligent Agent

Agent Service Discovery and Auto-Configuration

See Also: The Oracle Enterprise Manager Configuration Guide.

Debugging Tcl Scripts

The executable oratclsh is provided for debugging your Tcl scripts. Before executing oratclsh, set the environment variable TCL_LIBRARY to point to \$ORACLE_HOME/network/agent/tcl.

See Also: The *Oracle Enterprise Manager Application Developer's Guide* for additional details.
Index

Symbols

\$ using, 2-22 , 5-5 ? example of use, 2-9 @ to denote \$ORACLE_SID, 2-10 _editor setting, 4-6

A

Ada compiler, 2-10 ADA_PATH, 2-10 adapters utility, 6-3 ADDRESS specification protocol adapters, 6-5 administering SQL, 4-2 afiedt.buf, 4-7 asynchronous I/O, 3-5 using, 3-5 automatic login listener.ora file, 2-22 non-UNIX systems, 2-22 remote_os_roles, 2-27

В

BEQ protocol adapter, 6-5 ADDRESS, 6-6 overview, 6-5 syntax for connection parameters, 6-6 binding processes, 3-7 block and file size specifying, 3-9 BSD, 2-11 buffer cache size tuning, 3-9 buffer manager, 3-4

С

С Pro*C/C++, 5-4 cache size tuning, 3-9 catching routine example, 5-12 CATPROC.SQL, 1-15 CDE tools, 2-8 changing databases, 2-5 chmod command example, 2-21 cluster estimating size, 2-13 command interpreter, 2-11 commands expst, 3-8 impst, 3-8 ipcs, 3-5 orapwd, 2-25 sar, 3-4 vmstat, 3-4 common environment

oraenv file, 2-5 setting, 2-5 configuration files Net8, 6-3 precompiler, 5-3 CONNECT INTERNAL security, 2-21 control remote DBA access REMOTE_DBA_OPS_ALLOWED, 2-24 REMOTE_DBA_OPS_DENIED, 2-24 control remote login, 2-24 OPS_DOLLAR_LOGIN_DENIED, 2-24 COPY command SQL*Plus, 4-8 coraenv, 2-9 CPU usage priority level of processes, 3-7 processor binding, 3-7 single-task architecture, 3-8 tuning, 3-7

D

daemon user security, 2-23 database administrator permissions for executables, 2-20 files authorization. 2-21 security, 2-21 database I/O DBWR tuning, 3-5 database writer tuning, 3-5 dba group members. 2-19 relinking, 2-20 DBA group ID keywords, 2-23 non-default name, 2-24 DBA_GROUP /etc/listener.ora file, 2-24 DBA GROUP sid /etc/listener.ora file, 2-24

DBWR

tuning, 3-5 debugger programs, 5-3 default directory, 2-10, 2-11 linker option, 2-10 printer, 2-10 default printer, 2-11 default settings system editor, 4-7 demonstration precompiler, 2-30 the procedural option, PL/SQL, 2-29 demonstration programs oracle call interface, 5-6 Pro*C/C++, 5-4 demonstration tables creating manually, 4-4 deleting, 4-4 SOL*Plus, 4-3 disk monitoring performance, 3-6 quotas, 2-13 Disk I/O tuning, 3-5 disk I/O asynchronous I/O, 3-5 I/O slaves, 3-6 tuning the database writer, 3-5 disk performance issues, 3-7 DISPLAY environment variable, 2-10 dynamic and static linking oracle libraries, 5-9

Ε

echo command, 2-4 editor setting the order of, 4-6 SQL*Plus, 4-6 environment variables ADA_PATH, 2-10 DISPLAY, 2-10

HOME, 2-10 LANG, 2-10 LANGUAGE, 2-10 LD_LIBRARY_PATH, 2-10 LDOPTS, 2-10 LDPATH, 2-10 LPDEST, 2-10 NLS LANG, 2-7 ORA_NLS, 2-7 ORACLE_HELP, 2-8 ORACLE_HOME, 2-8 ORACLE_SID, 2-8 ORACLE_TERM, 2-8 ORACLE_TERMINAL, 2-9ORACLE_TRACE, 2-9 ORAENV_ASK, 2-9 PATH, 2-11 PRINTER, 2-11 setting for SQL*Plus, 4-6 SHELL, 2-11 TERM, 2-11 TMPDIR, 2-11 TNS_ADMIN, 2-9, 6-3 TWO_TASK, 2-9 TZ, 2-11 XENVIRONMENT, 2-11 exclamation point SQL*Plus prompt, 4-7 executable program, 2-11 exports tuning, 3-8 expst command, 3-8

F

file names default extensions in SQL*Plus, 4-8 files trace files, 3-10

G

glogin.sql, 4-2 groups sample script, 2-29

Η

help facility SQL*Plus, 4-4 help file, 2-8 HOME, 2-10 home directory, 2-10

I

I/O DBWR tuning, 3-5 tuning, 3-5 I/O slaves, 3-6 imports tuning, 3-8 impst command, 3-8 index size calculating, 2-13 initialization parameters BACKGROUND_DUMP_DEST, 2-14 BITMAP_MERGE_AREA_SIZE, 2-14 COMMIT_POINT_STRENGTH, 2-14 CONTROL_FILES, 2-14 CREATE_BITMAP_AREA_SIZE, 2-14 DB BLOCK BUFFERS, 2-14 DB_BLOCK_SIZE, 2-14 DB_FILE_DIRECT_IO_COUNT, 2-14 DB_FILE_MULTIBLOCK_READ_COUNT, 2-14 DB_FILES, 2-14 defaults, 2-14 DISTRIBUTED_TRANSACTIONS, 2-14 HASH_AREA_SIZE, 2-14 HASH_MULTIBLOCK_IO_COUNT, 2-14 LOCK_SGA, 2-15 LOCK_SGA_AREAS, 2-15 LOG_ARCHIVE_BUFFER_SIZE, 2-15 LOG_ARCHIVE_BUFFERS, 2-15 LOG_ARCHIVE_DEST, 2-15 LOG_ARCHIVE_FORMAT, 2-15 LOG_BUFFER, 2-15 LOG_CHECKPOINT_INTERVAL, 2-15 LOG_SMALL_ENTRY_MAX_SIZE, 2-15 MTS_LISTENER_ADDRESS, 2-15 MTS_MAX_DISPATCHERS, 2-15

MTS_MAX_SERVERS, 2-15 MTS_SERVERS, 2-15 NLS_LANGUAGE, 2-15 NLS_TERRITORY, 2-15 OBJECT_CACHE_MAX_SIZE_PERCENT, 2-15 OBJECT_CACHE_OPTIMAL_SIZE, 2-15 OPEN_CURSORS, 2-15 OS AUTHENT PREFIX, 2-15 PROCESSES, 2-15 REMOTE_OS_AUTHENT, 2-23 SHARED_POOL_SIZE, 2-15 SHOW PARAMETERS command, 2-14 SORT_AREA_SIZE, 2-15 SORT_READ_FAC, 2-15 SORT_SPACEMAP_SIZE, 2-15 USER_DUMP_DEST, 2-15 input and output, 2-10 interrupting SQL*Plus, 4-7 IPC protocol adapter, 6-7 ADDRESS, 6-7 overview. 6-7 ipcs command, 3-5 ireclen, 5-3

Κ

kernel tuning UNIX parameters, 3-8 keywords DBA group ID, 2-23

L

LANGUAGE environment variable, 2-10 language, 2-7 ld, 2-10 LD_LIBRARY_PATH environment variable, 2-10 LDOPTS environment variable, 2-10 LDPATH environment variable, 2-10 limits resource, 2-13 linking single-task, 3-8 login home directories administering, 2-27 sample script, 2-28 login.sql, 4-2 LPDEST environment variable, 2-10

М

MAXDATAFILES parameter, 2-34 MAXINSTANCES parameter, 2-34 MAXLOGFILES parameter, 2-34 MAXLOGHISTORY parameter, 2-34 MAXLOGMEMBERS parameter, 2-34 memory estimating usage, 2-12 SGA tuning, 3-5 shared, 2-15 tuning, 3-3 virtual, 2-12 memory management, 3-3 control paging, 3-4 single shared memory segment, 3-5 swap space, 3-4 UNIX kernel, 3-5 multiple databases shared password file, 2-26 multiple signal handlers, 5-12 multi-thread server, 6-4

Ν

naming adapters, 6-9 National Language Support (NLS) variable, 2-7 Net8 adapters utility, 6-3 automatic logins, 2-23 BEQ protocol adapter, 6-5 files and utilities, 6-3 IPC protocol adapter, 6-7 multi-thread server, 6-4 naming adapters, 6-9 oracle connection manager, 6-4 oracle enterprise manager intelligent agent, 6-9 oracle names, 6-4 products and features, 6-3 protocol adapters, 6-4 README files, 6-2 TCP/IP protocol adapter, 6-8 Net8 configuration files location of, 6-3 network dba privileges, 2-22 passwords, 2-22 security, 2-22 NLS_LANG environment variable, 2-7

0

operating system commands running from SQL*Plus, 4-7 ORA_NLS environment variable, 2-7 Oracle memory usage, 2-13 oracle account set authorization. 2-21 oracle call interface, 5-6 demonstration programs, 5-6 user programs, 5-7 using, 5-6 oracle connection manager, 6-4 oracle enterprise manager intelligent agent, 6-9 agent service discovery and auto-configuration, 6-9 debugging tcl scripts, 6-9 Oracle environment variables EPC_DISABLED, 2-7 NLS LANG. 2-7 ORA_NLS33, 2-7 ORACLE_BASE, 2-8 ORACLE_HELP, 2-8 ORACLE_HOME, 2-8 ORACLE_PATH, 2-8 ORACLE_SID, 2-8 ORACLE TERM, 2-8 ORACLE_TERMINAL, 2-9

ORACLE_TRACE, 2-9 ORAENV_ASK, 2-9 TNS_ADMIN, 2-9 TWO_TASK, 2-9 oracle group permissions and executables, 2-20 oracle libraries oracle shared library, 5-10 static and dynamic linking. 5-9 oracle names, 6-4 oracle precompiler and OCI linking and makefiles, 5-8 custom makefiles. 5-8 undefined symbols, 5-9 Oracle Server accounts. 2-19 oracle software owner, 2-19 special accounts, 2-19 Oracle System Identifier, 2-8 ORACLE HELP environment variable, 2-8 ORACLE HOME environment variable, 2-8 using? for, 2-9 ORACLE_SID environment variable, 2-8 suppressing prompt, 2-6 ORACLE_TERM environment variable, 2-8 oraenv file description, 2-5 moving between databases, 2-5 ORAENV ASK, 2-9 setting, 2-6 orainst, 2-8 orapwd command, 2-25 oreclen. 5-3

Ρ

paging space tuning, 3-3, 3-4 password files shared, 2-26 passwords remote, 2-25 PATH. 2-11 permissions dba group, 2-20 granting, 2-20 PL/SOL demonstrations loading, 2-29 precompiler relinking executables, 5-2 running demonstration, 2-30 value of ireclen and oreclen, 5-3 precompiler configuration files, 5-3 precompilers overview, 5-2 signals, 5-12 uppercase to lowercase conversion, 5-3 values, 5-3 vendor debugger programs, 5-3 preface Send Us Your Comments, vii PRINTER. 2-11 Pro*C/C++ administering, 5-4 demonstration programs, 5-4 makefiles, 5-4, 5-5 signals, 5-12 system configuration file, 5-4 user programs, 5-5 using, 5-4 PRODUCT_USER_PROFILE Table SOL*Plus, 4-3 protocol adapters, 6-4 ADDRESS specification, 6-5 pupbld.sql, 4-3

Q

question mark example of use, 2-9

R

raw devices buffer cache size, 3-9 README files

Net8. 6-2 related documentation, xii relinking precompiler executables, 5-2 remote connect as INTERNAL, 2-26 as OPERATOR, 2-26 login security, 2-23 parameter REMOTE_OS_AUTHENT, 2-23 remote connections parameters OS_AUTHENT_PREFIX, 2-27 REMOTE_OS_AUTHENT, 2-27 REMOTE_OS_ROLES, 2-27 resource contention kernel parameters, 3-8 tuning, 3-8 resource definition, 2-11 resource limits, 2-13 restrictions (SOL*Plus). 4-8 COPY command, 4-8 resizing windows, 4-8 return codes, 4-8 root user, 2-19

S

sar command, 3-4 security assigning permissions, 2-20 CONNECT INTERNAL, 2-21 default group names, 2-20 file ownership, 2-20 group accounts, 2-20 network. 2-22 Server Manager access, 2-21 SHUTDOWN command. 2-21 STARTUP command. 2-21 two-task architecture, 2-20 Send Us Your Comments boilerplate, vii Server Manager commands, 2-21

security, 2-21 SHOW PARAMETERS, 2-14 setup files SQL*Plus, 4-2 SGA estimating size, 3-5 relocating, 2-17 tuning, 3-5 shadow process security, 2-20 shared library loader, 2-10 object library, 2-10 shared memory SGA, 2-15 SGA tuning, 3-5 shared object library, 2-10 SHELL, 2-11 SHUTDOWN command, 2-21 security, 2-21 SIGCLD two-task signal, 5-12 SIGINT two-task signal, 5-12 SIGIO two-task signal, 5-12 signal handlers signals, 5-11 using, 5-11 signal routine example, 5-12 signals creating handlers, 5-11 two-task, 5-11 SIGPIPE two-task signal, 5-12 SIGTERM two-task signal, 5-12 SIGURG two-task signal, 5-12 single shared memory segment, 3-5 site profile SQL*Plus, 4-2 software distribution, 2-8 Solaris 2.x tools, 3-2 swap, 3-3 vmstat, 3-2 special accounts, 2-19 special groups root, 2-19 SPOOL command

SOL*Plus, 4-8 using, 4-8 SQL administering, 4-2 SQL scripts, 3-3 utlbstat and utlestat, 3-3 SQL*DBA, 2-8 SHOW PARAMETERS, 2-14 SOL*Plus COPY command, 4-8 default editor, 4-6 demonstration tables. 4-3 editor, 4-6 environment variables, 4-6 help facility, 4-4 interrupting, 4-7 PRODUCT_USER_PROFILE Table, 4-3 restrictions, 4-8 sample setup files, 4-3 setup files, 4-2 site profile, 4-2 SPOOL command, 4-8 system editor, 4-6 UNIX commands, 4-7 user profile, 4-2 using, 4-6 STARTUP command security, 2-21 static and dynamic linking oracle libraries, 5-9 sub-shell creating in SQL*Plus, 4-7 superuser, 2-19 swap, 3-3 swap space tuning, 3-3 SYS account privileges, 2-19 SYSDATE and TZ, 2-12 SYSTEM account privileges, 2-19 system configuration file Pro*C/C++, 5-4 system editor

default settings, 4-7 setting the order of, 4-6 SQL*Plus, 4-6 System Global Area (SGA) relocating, 2-17 requirements, 2-15 system time setting, 2-11 System V, 2-10

Т

TCP/IP protocol adapter, 6-8 ADDRESS, 6-8 overview, 6-8 temporary disk file, 2-11 TERM environment variable, 2-11 thread support, 5-9 time zone setting with TZ, 2-11 TMPDIR, 2-11 TNS listener configuring for Oracle TCP/IP Protocol Adapter, 6-8 TNS_ADMIN environment variable, 2-9 Toolkit II resource file, 2-9 tools. 3-2 trace and alert files alert files, 3-10 trace file names, 3-10 using, 3-9, 3-10 tracing Bourne shell scripts, 2-9 tuning block and file size, 3-9 CPU usage, 3-7 disk I/O. 3-5 I/O bottlenecks, 3-5 memory management, 3-3 resource contention. 3-8 Solaris 2.x buffer cache size, 3-9 trace and alert files, 3-9, 3-10 TWO_TASK environment variable, 2-9 two-task

architecture security, 2-20 signals, 5-11 TZ and SYSDATE, 2-11 environment variable, 2-11

U

UNIX security, 2-20 UNIX commands running from SQL*Plus, 4-7 UNIX environment variables used with Oracle8 ADA_PATH, 2-10 DISPLAY, 2-10 HOME, 2-10 LANG, 2-10 LD_LIBRARY_PATH, 2-10 LDOPTS, 2-10 LDPATH, 2-10 LPDEST, 2-10 PATH, 2-11 PRINTER, 2-11 SHELL, 2-11 TERM, 2-11 TMPDIR, 2-11 XENVIRONMENT, 2-11 UNIX kernel tuning, 3-8 user interrupt handler, 5-12 user profile SQL*Plus, 4-2 user programs oracle call interface, 5-7 Pro*C/C++, 5-5 users sample script, 2-29 using SQL*Plus, 4-6 utlbstat and utlestat SQL scripts, 3-3

V

vmstat, 3-2 vmstat command, 3-4

W

writer activity tuning, 3-5

Х

X Windows, 2-10, 2-11 XA functionality, 5-14 XENVIRONMENT environment variable, 2-11